

**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
RONBE	TWO	RONBE2.RONBE	ONE	09/18/2014	<b>15 AUG 2019</b>
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

**DP ROUTE DESCRIPTION:**

TAKEOFF RWY 24: CLIMB ON HEADING 241.67 TO 8023 THEN CLIMBING RIGHT TURN DIRECT UHIKI, THEN ON DEPICTED ROUTE TO RONBE, MAINTAIN 16200 OR ASSIGNED ALTITUDE, AIRCRAFT SOUTHWEST BOUND ON V160 CONTINUE CLIMB IN RONBE HOLDING PATTERN (NE, RT, 230.00 INBOUND, 10 MILE LEGS) TO MEA BEFORE PROCEEDING ENROUTE.

**TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):**

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

**PROCEDURAL DATA NOTES:**

NOTE: GPS REQUIRED.

NOTE: RNAV 1.

**TAKEOFF MINIMUMS:**

RWY 6: NA - OBSTACLES.

RWY 24: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 11500.

**TAKEOFF OBSTACLES NOTES:**

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

**CONTROLLING OBSTACLES:**

RWY 24: 10359 FT MSL AAO, 383642.40N/1061129.77W

**LOST COMMUNICATIONS PROCEDURES:****ADDITIONAL FLIGHT DATA:**

REFERENCE MAG VAR: KANK 9E EPOCH YEAR: 2010.

CHART: TOP ALTITUDE: 16200.

**AIRPORTS SERVED:**

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
SALIDA ARPT HARRIETT ALEXANDER FIELD (KANK)	SALIDA	CO

**COMMUNICATIONS:**

ZDV ARTCC

**FIXES AND/OR NAVAIDS:****REMARKS:**

ABBREVIATED AMENDMENT




**FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
RONBE	TWO	RONBE2.RONBE	ONE	09/18/2014	<b>15 AUG 2019</b>

**FLIGHT INSPECTED BY:**

PROCESSED IAW AIRCRAFT OPERATIONS GROUP  
(AJW-33) MEMO, OCTOBER 3, 2018,  
SUBJECT FLIGHT INSPECTION REVIEW NOT REQUIRED 

*Digitally signed by*

**CASIMIR L TABAKA**

Apr 10, 2019

**OFFICE SYMBOL:****DATE:****DEVELOPED BY:**

JASON KRETSCHMER

*Digitally signed by*

**CASIMIR L TABAKA**

Apr 10, 2019

**OFFICE SYMBOL:****DATE:**

AJV-A422

02/11/2019

**APPROVED BY:**

JULIE MORGAN

*Digitally signed by*

**CASIMIR L TABAKA**

Apr 10, 2019

**OFFICE SYMBOL:****DATE:**

AJV-A420

**REQUIRED EFFECTIVE DATE:**

ROUTINE

**COORDINATED WITH:**

A4A

ALPA

AOPA

APA

HAI

NBAA

**OTHER:**

ZDV ARTCC, AMGR

**CHANGES - REASONS:**

- AIRPORT NAME CHANGED FROM "HARRIET ALEXANDER FIELD" TO "SALIDA ARPT HARRIETT ALEXANDER FIELD". - AIRNAV DATA CHANGE.
- CHANGED DEPARTURE ROUTE DESCRIPTION FROM "TAKEOFF RWY 24: CLIMB ON HEADING 241.66 TO 8023 THEN CLIMBING RIGHT TURN DIRECT UHIKI, THEN ON DEPICTED ROUTE TO RONBE, MAINTAIN 16200 OR ASSIGNED ALTITUDE, AIRCRAFT SOUTHWEST BOUND ON V160 CONTINUE CLIMB IN RONBE HOLDING PATTERN (NE, RT, 230.00 INBOUND) TO MEA BEFORE PROCEEDING ENROUTE" TO "TAKEOFF RWY 24: CLIMB ON HEADING 241.67 TO 8023 THEN CLIMBING RIGHT TURN DIRECT UHIKI, THEN ON DEPICTED ROUTE TO RONBE, MAINTAIN 16200 OR ASSIGNED ALTITUDE, AIRCRAFT SOUTHWEST BOUND ON V160 CONTINUE CLIMB IN RONBE HOLDING PATTERN (NE, RT, 230.00 INBOUND, 10 MILE LEGS) TO MEA BEFORE PROCEEDING ENROUTE". - RWY 24 THLD LAT/LONG CHANGED.
- REPLACED TAKEOFF OBSTACLE NOTES WITH "SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)". - IAW MEMO 259/8260.46F WAIVER.
- REMARKS: ADDED ABBREVIATED AMENDMENT. - IAW 8260.46F DOCUMENTATION CRITERIA FOR ABBREVIATED AMENDMENT.
- CHANGED RW24 THLD LAT/LONG FROM 383229.85N/1060211.46W TO 383229.85N/1060211.42W IN DEPARTURE (DATA RECORD). - AIRNAV DATA CHANGE.
- CHANGED RW24 TRUE COURSE FROM 250.66 TO 250.67 IN DEPARTURE (DATA RECORD). - AIRNAV DATA CHANGE.
- UPDATED 82630-15C TO INCLUDE CODING FOR CLIMB-IN-HOLD PROCEDURE. - ARINC 424 CODING.
- ADDED NOTE "CHART: TOP ALTITUDE: 16200" TO ADDITIONAL FLIGHT DATA. - REQUIRED TO SUPPORT ATC OPERATIONAL POLICY IAW 8260.46F.

QUALITY  
3  
CHECKED

FEDERAL AVIATION ADMINISTRATION  
FLIGHT STANDARDS SERVICE  
DEPARTURE (DATA RECORD)

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
RONBE		TWO		RONBE2. RONBE		ONE		09/18/2014	<b>15 AUG 2019</b>
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW24	383229.85N/1060211.42W	N	-	-	-	-			
8023 MSL		-	-	-	250.67	-			
UHIKI	384026.00N/1060529.00W	Y	FB	DF	-	-			RIGHT TURN
RONBE	385150.17N/1055647.70W	Y	FB	TF	030.77	13.26			

QUALITY  
3  
CHECKED