DOT/FAA IAPA FORM 8260-5 VOR STANDARD INSTRUMENT APPROACH PROCEDURE

FAR 97.23 PAGE 1 OF 1

AIRPORT: TETERBORO SIAP: VOR RWY 24 SUP:NONE RUNWAY: R24 TDZ ELEV:8

CITY:TETERBORO AMDT:0 AMDT:NONE FACILITY: TEB VOR/DME

STATE:NJ APT ELEV:9 EFFECTIVE DATE: 02-FEB-95 EFFECTIVE DATE: FAC ELEV:10 FAC VARIATION: 11

YEAR: 1965

FROM

TO

COURSE DISTANCE ALTITUDE

STRAIGHT INTERMEDIATE

IAF ABEAN INT/10.50 DME

ANGLE INT/5.50 DME

(TEB R-051)

231.38 5.00

1500

RADAR REQUIRED

PROCEDURE TURN IS N/A. PROFILE STARTS AT ABEAN

FAC:231.38 FAF:ANGLE INT/5.50 DME DIST FAF TO: MAP: TH LD: 4.85 DIST SOF TO: MAP: TH LD: MIN ALT:ABEAN, 2000 ,; ANGLE INT/5.50 DME, 1500 .

MAP:TEB VOR/DME MISSED APPROACH:

> CLIMBING RIGHT TURN TO 1500 VIA TEB R-260 TO 3 DME THEN CLIMB TO 2000 DIRECT CAT NDB AND HOLD.

MA HOLDING: HOLD SW, LEFT TURN, 035.00 INBOUND

MSA: FROM TEB WOR/DME , WITHIN 25.00 , 2900

INIMUMS	A			В			C			D			Ε .		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
-R24	500	1	492	500	1	492	500	1.25	492	500	1.5	492	THE RODINGS	N/A	
IRCLING	760	1	751	1000	1.5	991	1000	3	991	1000	3	991		N/A	

TAKEOFF MINIMUMS:SEE 8260-15 FOR THIS AIRPORT

ALTERNATE MINIMUMS:STANDARD* *CATS B,C,D 1000-3

NOTES:

CIRCLING NA CATS B,C AND D NW OF RWY 6 AND 19 ADF REQUIRED

ADDITIONAL FLIGHT DATA:

FAS OBST: 240' OL STACK 405210/740159 FAC CROSSES RWY C/L EXTENDED 3000' FROM THLD. CHART: 936' TOWER 405738/735521

BEARINGS, HEADINGS, COURSES AND RADIALS ARE MAGNETIC. ELEVATIONS AND ALTITUDES ARE IN FEET, MSL, EXCEPT HAT, HAA, AND RA. ALTITUDES ARE MINIMUM ALTITUDES UNLESS OTHERWISE INDICATED. CEILINGS ARE IN FEET ABOVE AIRPORT ELEVATION. DISTANCES ARE IN NAUTICAL MILES UNLESS OTHERWISE INDICATED, EXCEPT VISIBILITIES WHICH ARE IN STATUTE MILES OR IN FEET RVR.