

**RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES**

**MISSED APPROACH**

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
WIGXO (IAF)	VAGXA (NOPT) (TF) (FB) (RNP 1.00)	316.67 / 5.71	2900	LPV: DA LNAV/VNAV: DA LNAV: RW22R
PAZYA (IAF)	VAGXA (NOPT) (TF) (FB) (RNP 1.00)	136.58 / 5.00	2900	CLIMB TO 2900 DIRECT RIWLO AND ON TRACK 221.07 TO BAUDE AND HOLD.
VAGXA (IF/IAF)	ODXIH (TF) (FB) (RNP 1.00)	226.62 / 6.27	2100	
ODXIH (FAF)	RW22R (MAP) (TF) (FO) (RNP 0.30)	226.57 / 5.50		ADDITIONAL FLIGHT DATA: HOLD SW, LT, 052.00 INBOUND. CHART FAS OBST: 475 TOWER 344551N/0921156W, 402 POLE 344509N/0921253W. CHART: ASR. DISTANCE TO THLD FROM 200 HAT: 0.44 NM. CHART VDP AT 1.32 NM TO RW22R* *LNAV ONLY. WAAS CHANNEL # 93811 REFERENCE PATH ID: W22B CHART CIRCLING ICON. LTP HAE: 53.1 M
RW22R (MAP)	462 MSL (CA)	226.57		
(SEE FORM 8260-10)				

1. PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. HOLD NE VAGXA, RT, 226.62 INBOUND, 2900 FT. IN LIEU OF PT (IAF)
3. FAC: 226.57 FAF: ODXIH DIST FAF TO MAP: 5.50 THLD: 5.50
4. MIN. ALT: VAGXA 2900, ODXIH 2100
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
6. MIN GS INCPT: 2100 GS ALT AT: ODXIH 2100 OM:        MM:        IM:
7. GS ANGLE: 3.00 TCH: 58.9 34:1 IS CLEAR
8. MSA FROM:

MAG VAR: 0E EPOCH YEAR: 2020

**MINIMUMS**

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	462	1800	200	462	1800	200	462	1800	200	462	1800	200			
LNAV/VNAV DA	727	5000	465	727	5000	465	727	5000	465	727	5000	465			
LNAV MDA	740	2400	478	740	2400	478	740	5000	478	740	5000	478			

CIRCLING	820	1	554	1000	1	734	1180	2 3/4	914	1180	3	914			

NOTES:  
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). @ CAT C 1000-2 3/4, CAT D 1000-3  
CHART NOTE: DME/DME RNP-0.3 NA.



CITY AND STATE LITTLE ROCK, AR	ELEVATION: 266 TDZE: 262 AIRPORT NAME: BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22R, AMDT 1C 19 JULY 2018	SUP: AMDT: 1B DATED 03/05/2015
-----------------------------------	--	------------------------------	---	--------------------------------------

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
462 MSL	RIWLO (DF) (FB) (RNP 1.00)		
RIWLO	BAUDE (TF) (FO) (RNP 1.00)	221.07 / 12.80	2900

**TAA**

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	137/30 CW 317/30 (NOPT)	VAGXA (IF/IAF) (FB)	2900
2.	317/30 CW 047/30	WIGXO (IAF) (FB)	3300
3.	047/30 CW 137/30	PAZYA (IAF) (FB)	3300

QUALITY  
20  
CHECKED

CITY AND STATE <b>LITTLE ROCK, AR</b>	ELEVATION: 266      TDZE: 262 AIRPORT NAME: <b>BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 22R, AMDT 1C</b> 19 JULY 2018	SUP:
				AMDT: <b>1B</b>
				DATED: <b>03/05/2015</b>

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION**

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KLIT
RUNWAY	RW22R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W22B
LTP/FTP LATITUDE	344417.3560N
LTP/FTP LONGITUDE	0921304.9770W
LTP/FTP ELLIPSOIDAL HEIGHT	+00531
FPAP LATITUDE	344315.9300N
FPAP LONGITUDE	0921423.4000W
THRESHOLD CROSSING HEIGHT (TCH)	00058.9
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0232
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 470940E6

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00797
FPAP ORTHOMETRIC HEIGHT	+00797



CITY AND STATE <b>LITTLE ROCK, AR</b>	ELEVATION: 266 AIRPORT NAME: <b>BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD</b>	TDZE: 262	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 22R, AMDT 1C</b> 19 JULY 2018	SUP:
					AMDT: <b>1B</b>
					DATED: <b>03/05/2015</b>