

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> PRAGUE MUNI	<u>AIRPORT ID</u> O47	<u>PROCEDURE NAME</u> RNAV (GPS)-A	<u>ORIGINAL/AMENDMENT</u> ORIG-A	<u>CITY</u> PRAGUE	<u>STATE</u> OK	
<u>AIRPORT ELEVATION</u> 1041	<u>TDZE</u>	<u>SUPERSEDED</u> RNAV (GPS)-A	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>DATED</u> 05/29/2014	<u>MAG VAR</u> 3E	<u>EPOCH YEAR</u> 2015
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 20 JUNE 2019	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TAA

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>ALTITUDE</u>
1. 287/30 CW 067/30	NOPT	VIRUJ	IF/IAF	3000
2. 067/30 CW 177/30		WATOM	IAF	3100
3. 177/30 CW 287/30		XETJO	IAF	3000

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
WATOM	IAF	VIRUJ	NOPT	TF	FB	1.00	067.22	5.00	3000
XETJO	IAF	VIRUJ	NOPT	TF	FB	1.00	287.34	5.00	3000
VIRUJ	IF/IAF	YADUG		TF	FB	1.00	357.28	5.00	2600
YADUG	FAF	RW35	MAP	TF	FO	0.30	357.28	4.87	
RW35	MAP	1441 MSL		CA			357.28		
1441 MSL		REXEC		DF	FO	1.00			3000

MISSED APPROACH

MAP:
RW35

MISSED APPROACH INSTRUCTIONS:
CLIMB TO 3000 DIRECT REXEC AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. HOLD S VIRUJ, RT, 357.28 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 6000.

3. FAC: 357.28

FAF: YADUG

DIST FAF TO MAP: 4.87

DIST FAF TO THLD: 4.87

4. MIN ALT: VIRUJ 3000, YADUG 2600

5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:

6. MIN GP INCPT:

GP ALT AT FAF :

OM:

MM:

IM:

7. GP ANGLE:

34:1: IS NOT CLEAR

20:1: IS NOT CLEAR

TCH:

8. MSA FROM:

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.
CHART NOTE: USE SHAWNEE ALTIMETER SETTING. WHEN NOT RECEIVED, USE SEMINOLE ALTIMETER SETTING.

ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON
CHART FAS OBST: 1375 TOWER 352643N/0964207W.
CHART: 1245 TOWER 352341N/0964227W.
HOLD N, RT, 177.27 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
CIRCLING	1480	1	439	1500	1	459	1720	2	679		NA				

CHANGES - REASONS

1. REMOVED CHART NOTE "DME/DME RNP-0.3 NA" REMOVED - 8260.19H 4-6-10.E.
2. ADDED "CHART NOTE PBN REQUIREMENTS NOTE: RNP APCH" ADDED - 8260.19H 8-6-8.
3. CIRCLING CAT C MDA/HAA CHANGED FROM 1480/438 TO 1500/459. - NEW OBSTACLE. NOTAM !FDC 8/3848.
4. ADDED 20:1 IS NOT CLEAR - INCLUDED ON NEW FORM.
5. REMOVED HELICOPTER CHART NOTE - NO LONGER REQUIRED, HELICOPTER NOTE ONLY APPLIES TO STRAIGHT-IN RUNWAY.



AIRPORT
PRAGUE MUNI

AIRPORT ID
O47

PROCEDURE NAME
RNAV (GPS)-A

ORIGINAL/AMENDMENT
ORIG-A

CITY
PRAGUE

STATE
OK

COORDINATED WITH:

A4A ☐ ALPA ☐ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZFW, AMGR

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

DEVELOPED BY

FRANK MOORE

Digitally signed by

FRANK MOORE

Feb 08, 2019

OFFICE

Digitally signed by

DATE

DAVID TEFFETELLER

Feb 26, 2019

OFFICE

AJV-A433

DATE

01/29/2019

APPROVED BY

PATRICK MULQUEEN

Digitally signed by

DAVID TEFFETELLER

Feb 26, 2019

OFFICE

AJV-A43

DATE

TITLE

MANAGER