

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> PERRY STOKES	<u>AIRPORT ID</u> KTAD	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 3	<u>ORIGINAL/AMENDMENT</u> 1B	<u>CITY</u> TRINIDAD	<u>STATE</u> CO
<u>AIRPORT ELEVATION</u> 5762	<u>TDZE</u> 5757	<u>SUPERSEDED</u> RNAV (GPS) RWY 3	<u>ORIGINAL/AMENDMENT</u> 1A	<u>DATED</u> 08/21/2014	<u>MAG VAR</u> 10E
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 20 JUNE 2019	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>	<u>EPOCH YEAR</u> 1995

TERMINAL ROUTES **THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 19-11.**

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
TATKE	IAF	HARVO		TF	FB	1.00	077.32	4.63	10400
HARVO	IF	JOSAT		TF	FB	1.00	044.91	9.00	9000
JOSAT	FAF	WAXOX/7.40 NM TO RW03		TF	FB	0.30	034.81	2.35	
WAXOX/7.40 NM TO RW03		YUBVU/3.80 NM TO RW03		TF	FB	0.30	034.81	3.60	
YUBVU/3.80 NM TO RW03		RW03	MAP	TF	FO	0.30	034.81	3.80	
RW03	MAP	6162 MSL		CA			034.81		
6162 MSL		JOCEL		DF	FO	1.00			8900

MISSED APPROACH

MAP:

LNAV: RW03

MISSED APPROACH INSTRUCTIONS:

CLIMBING LEFT TURN TO 8900 DIRECT JOCEL AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. PROFILE STARTS AT HARVO

3. FAC:

034.81

FAF: JOSAT

DIST FAF TO MAP: 9.75

DIST FAF TO THLD: 9.75

4. MIN ALT: HARVO 10400, JOSAT 9000, WAXOX/7.40 NM TO RW03 8180, YUBVU/3.80 NM TO RW03 7040

5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:

6. MIN GP INCPT:

GP ALT AT FAF :

OM:

MM:

IM:

7. GP ANGLE:

34:1

IS CLEAR

20:1

IS CLEAR

TCH:

8. MSA FROM: RW03 13900

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 9 AND 27.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLE NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
CHART NOTE: VDP NA WHEN USING PUEBLO MEMORIAL ALTIMETER SETTING.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT TATKE ON V611 SOUTHBOUND.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECIEVED, USE PUEBLO MEMORIAL ALTIMETER SETTING AND INCREASE ALL MDAS 300 FT; INCREASE LNAV CATS A/B VISIBILITY 1/4 SM AND CATS C/D VISIBILITY 1 SM AND CIRCLING CATS A/B VISIBILITY 1/4 SM, CAT C 1 SM, AND CAT D 1/2 SM.

ADDITIONAL FLIGHT DATA:

JOSAT TO RW03: 3.10/36
CHART CIRCLING ICON.
CHART VDP AT 2.21 NM TO RW03
FAS OBST: 6240 AAO 371232N/1042313W.
7720 AAO 370731N/1042825W, 6800 AAO 370924N/1042656W.
HOLD N, RT, 166.48 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ STANDARD - CAT D 800-2 1/2

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	6500	1	743	6500	1 1/4	743	6500	2	743	6500	2	743			
CIRCLING	6500	1	738	6500	1 1/4	738	6500	2	738	6560	2 1/2	798			



CHANGES - REASONS

- 1. REMOVED CHART NOTE "DME/DME RNP-0.3 NA" AND ADDED "RNP APCH" IN PBN EQUIPMENT REQUIREMENT NOTES - UPDATE TO CURRENT CRITERIA IAW 8260.19H 8-6-8.B.(1).
- 2. UPDATED PLANVIEW NOTE FROM "PROCEDURE NA FOR ARRIVALS AT TATKE ON V611 SOUTBOUND" TO "PROCEDURE NA FOR ARRIVALS AT TATKE ON V611 SOUTHBOUND" - CORRECTED SPELLING FOR SOUTHBOUND AND INCORPORATED FDC NOTAM 8/7241.
- 3. ADDED NON-COINCIDENTAL VGSI NOTE - IAW 8260.19H 8-6-9.M.(1).
- 4. ADDED CHART NOTE "CIRCLING NA TO RWYS 9 AND 27" - MATCHED OPPOSITE RUNWAY'S CHART NOTE PER FPT.
- 5. REMOVED ALTERNATE ALTIMETER NOTE "NA WHEN LOCAL WEATHER NOT AVAILABLE" - LOCAL WEATHER IS ON WMSCR.
- 6. UPDATED CHART NOTE FROM "VDP NA WITH PUEBLO MEMORIAL ALTIMETER SETTING" TO "VDP NA WHEN USING PUEBLO MEMORIAL ALTIMETER SETTING" - IAW 8260.19H 8-6-9.E.(9).

04/24/2019: THIS IS S CORRECTED COPY OF THE FORM APPROVED ON 02/05/2019.
CHANGED PROFILE NOTE TO VGSI AND DESCENT ANGLE NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

COORDINATED WITH:

A4A ☐ ALPA ☐ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZDV, AMGR

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

DATE

Digitally signed by
CASIMIR L TABAKA
Apr 25, 2019

DEVELOPED BY

ROBERT G HAMILTON (MADELINE CLARK)

Digitally signed by
CASIMIR L TABAKA
Apr 25, 2019

OFFICE

AJV-5422

DATE

12/06/2018

APPROVED BY

ROBERT HAMILTON

Digitally signed by
CASIMIR L TABAKA
Apr 25, 2019

OFFICE

AJV-5422

DATE

TITLE
MANAGER

