

**Federal Aviation  
Administration**

**Transmittal Letter 19-06**

**January 25, 2019**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
28-Feb-19	IL	Bloomington/ Normal	Central Il Rgnl Arpt At Bloomington-Normal	8/2864	1/11/19	RNAV (GPS) RWY 2, Orig-B

**AIRAC Date: 28 FEBRUARY 2019**

FDC **8/2864** BMI IAP CENTRAL IL RGNL ARPT AT BLOOMINGTON-NORMAL, Bloomington/Normal, IL. RNAV (GPS) RWY 2, ORIG-B... DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT THEME ON V72 SOUTHEAST BOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT THEME ON V313 SOUTHBOUND. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING: INCREASE ALL DA 166 FT AND ALL MDA 120 FT; INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/2 MILE, LNAV CATS C/D VISIBILITY 3/8 MILE, AND CIRCLING ALL CATS VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING: INCREASE ALL DA 166 FEET AND ALL MDA 120 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/2 SM, LNAV CATS C/D VISIBILITY 3/8 SM, AND CIRCLING ALL CATS VISIBILITY 1/4 SM. DELETE NOTE: DME/DME RNP-0.3 NA PBN REQUIREMENTS NOTE: RNP APCH. THIS IS RNAV (GPS) RWY 2, ORIG-C. 1810261408-PERM