

**Federal Aviation
Administration**

Transmittal Letter 19-21

August 23, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/10/2019	KS	Iola	Allen County	9/4362	7/31/2019	RNAV (GPS) RWY 1, Amdt 1A

AIRAC Date: 10 OCTOBER 2019

FDC 9/4362 K88 IAP ALLEN COUNTY, Iola, KS. RNAV (GPS) RWY 1, AMDT 1A... MSA FROM RW01 2800. CIRCLING CAT C MDA 1660/HAA 644. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: RWY 1 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. DELETE NOTE: WHEN VGSI INOP, PROCEDURE NA AT NIGHT. CHART VDP AT 1.31 NM TO RW01* *LNAV ONLY. DELETE NOTE: BARO-VNAV NA WHEN USING CHANUTE ALTIMETER SETTING. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING CHANUTE ALTIMETER SETTING. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHANUTE ALTIMETER SETTING AND INCREASE ALL DA 32 FEET AND ALL MDA 40 FEET. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHANUTE ALTIMETER SETTING: INCREASE ALL DA TO 1296 FEET; INCREASE ALL MDAS 40 FEET AND VISIBILITY CIRCLING CAT C 1/4 SM. ALTERNATE MINIMUMS: STANDARD. THIS IS RNAV (GPS) RWY 1, AMDT 1B. 1904191420-PERM