

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> DETROIT METROPOLITAN WAYNE COUNTY	<u>AIRPORT ID</u> KDTW	<u>PROCEDURE NAME</u> RNAV (RNP) X RWY 4L	<u>ORIGINAL/AMENDMENT</u> ORIG-A	<u>CITY</u> DETROIT	<u>STATE</u> MI
<u>AIRPORT ELEVATION</u> 645	<u>TDZE</u> 645	<u>SUPERSEDED</u> RNAV (RNP) X RWY 4L	<u>ORIGINAL/AMENDMENT</u> ORIG	<u>DATED</u> 05/24/2018	<u>MAG VAR</u> 7W
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 10 OCTOBER 2019	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>	<u>EPOCH YEAR</u> 2020

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
SSHEE	IAF	NUMMM		TF	FB	1.00	218.87	3.65	3500
NUMMM		TRNST		RF	FB	1.00	(3.12 NM RADIUS CCW (CFDSP))	4.62	3000
GRBAC	IAF	TRNST		TF	FB	1.00	133.94	5.15	3000
TRNST		CORBI		RF	FB	1.00	(3.12 NM RADIUS CCW (CFDSP))	0.96	3000
CORBI		ASLLI		RF	FB	1.00	(3.12 NM RADIUS CCW (CFDSP))	4.39	3000
SIZOR	IAF	PAYLE		TF	FB	1.00	113.50	6.13	4000
PAYLE		ACIRA		RF	FB	1.00	(3.40 NM RADIUS CCW (CFBTK))	4.63	4000
NBSTN	IAF	ACIRA		TF	FB	1.00	035.54	2.09	4000
ACIRA		ASLLI		TF	FB	1.00	035.55	3.14	3000
ASLLI		NATYI		TF	FB	1.00	035.58	4.20	3000
NATYI		REGGE		TF	FB	1.00	035.61	3.14	3000
REGGE	IF	PAYED	PFAF	TF	FB	1.00	035.63	3.14	2000
PAYED	PFAF	RW04L	MAP	TF	FO	0.30	035.65	4.08	
RW04L	MAP	1100 MSL		CA			035.65		1100
1100 MSL		DOHNT		DF	FO	1.00			4000



