

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> ELTON HENSLEY MEMORIAL	<u>AIRPORT ID</u> KFTT	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 18	<u>ORIGINAL/AMENDMENT</u> ORIG-C	<u>CITY</u> FULTON	<u>STATE</u> MO
<u>AIRPORT ELEVATION</u> 887	<u>TDZE</u> 881	<u>SUPERSEDED</u> RNAV (GPS) RWY 18	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>DATED</u> 01/03/2019	<u>MAG VAR</u> 1E
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 25 APRIL 2019	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>	<u>EPOCH YEAR</u> 2010

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
MEMAC	IAF	YAKUY	NOPT	TF	FB	1.00	270.00	23.42	3000
HLV VORTAC	IAF	YAKUY	NOPT	TF	FB	1.00	128.96	8.31	3000
YAKUY	IF/IAF	ZENIS		TF	FB	1.00	180.93	6.10	2500
ZENIS	FAF	ZIRAM/2.50 NM TO RW18		TF	FB	0.30	180.92	2.40	
ZIRAM/2.50 NM TO RW18		RW18	MAP	TF	FO	0.30	180.92	2.50	
RW18	MAP	1155 MSL		CA			180.92		
1155 MSL		UYURO		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LPV: DA
 LNAV/VNAV: DA
 LNAV: RW18

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 DIRECT UYURO AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF (IAF)				
2.	HOLD N YAKUY, RT, 180.93 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 6000.							
3. FAC:	180.92	FAF: ZENIS	DIST FAF TO MAP: 4.90	DIST FAF TO THLD: 4.90				
4. MIN ALT:	YAKUY 3000, ZENIS 2500, ZIRAM/2.50 NM TO RW18 1720*							
5. DIST TO THLD FROM OM:	MM:	IM:	150 HAT:	274 HAT: 0.74	GS ANT:			
6. MIN GP INCPT: 2500	GP ALT AT FAF : ZENIS 2500				OM:	MM:	IM:	
7. GP ANGLE: 3.00	34:1:	IS NOT CLEAR	20:1:	IS NOT CLEAR	TCH: 42.0			
8. MSA FROM:	RW18 3100							

PBN REQUIREMENTS NOTE:

RNP APCH

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 12 AND 30.
CHART NOTE: CIRCLING RWY 24 NA AT NIGHT.
CHART NOTE: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
CHART NOTE: BARO-VNAV NA.
*LNAV ONLY
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON HLV VORTAC AIRWAY RADIALS 039 CW 219.
CHART NOTE: USE COLUMBIA ALTIMETER SETTING; WHEN NOT RECEIVED USE JEFFERSON CITY ALTIMETER SETTING AND INCREASE ALL DA 62 FEET, ALL MDA 80 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE, LNAV AND CIRCLING CAT C VISIBILITY 1/4 MILE.

ADDITIONAL FLIGHT DATA:

CHART COLUMBIA RGNL ASOS.
CHART CIRCLING ICON.
WAAS CHANNEL #42611
REFERENCE PATH ID: W18A
CHART FAS OBST: 1244 TOWER 385242N/0915855W.
CHART 1302 TOWER 385430N/0915924W.
HOLD S, RT, 000.92 INBOUND
LTP HAE: 235.1 M



MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LPV DA	1155	1	274	1155	1	274	1155	1	274		NA				
LNAV/VNAV DA	1313	1 1/2	432	1313	1 1/2	432	1313	1 1/2	432		NA				
LNAV MDA	1520	1	639	1520	1	639	1520	1 3/4	639		NA				
CIRCLING	1520	1	633	1520	1	633	1560	2	673		NA				

CHANGES - REASONS
- MOVED CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C TO BACK OF -9 FOR INFORMATIONAL PURPOSES.
- ADDED CHART COLUMBIA RGNL AWOS-3 TO ADDITIONAL FLIGHT DATA.

THIS AMENDMENT CANCELS FDC NOTAM 9/6667.

COORDINATED WITH:
A4A ☐ **ALPA** ☒ **AOPA** ☒ **APA** ☐ **HAI** ☐ **NBAA** ☒ **OTHER:** MIZZU APP CON, ZKC, AMGR

FLIGHT CHECKED BY
PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

DEVELOPED BY
STEVEN M. BARNETT

APPROVED BY
JULIE MORGAN

Digitally signed by
STEVEN M BARNETT
Mar 14, 2019

Digitally signed by
CASIMIR L TABAKA
Mar 15, 2019

OFFICE
AJV-A422

OFFICE
AJV-A420

DATE
03/14/2019

DATE
TITLE
MANAGER



FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFTT
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	385027.5795N
LTP/FTP LONGITUDE	0915959.5290W
LTP/FTP ELLIPSOIDAL HEIGHT	+02351
FPAP LATITUDE	384858.4435N
FPAP LONGITUDE	0920003.3460W
THRESHOLD CROSSING HEIGHT (TCH)	00042.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER	0BBDD3C8
---------------	----------

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+02674
FPAP ORTHOMETRIC HEIGHT	+02674

