Federal Aviation Administration

Transmittal Letter 19-16

June 14, 2019

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	AL	Wetumpka	Wetumpka Muni	9/5067	6/4/2019	RNAV (GPS) RWY 9, Orig-B

AIRAC Date: 18 July 2019

FDC 9/5067 08A IAP WETUMPKA MUNI, Wetumpka, AL. RNAV (GPS) RWY 9, ORIG-B... DELETE CIRCLING MINIMUMS. DELETE NOTE: CIRCLING NA TO RWY 18-36. CHART NOTE: USE MONTGOMERY RGNL (DANNELLY FIELD) ALTIMETER SETTING; WHEN NOT RECEIVED, USE ALEXANDER CITY ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET AND INCREASE LNAV CAT A VISIBILITY 1/4 SM AND LNAV CAT C VISIBILITY 1/2 SM. DELETE NOTE: USE MONTGOMERY RGNL (DONNELLEY FIELD) ALTIMETER SETTING; WHEN NOT RECEIVED, USE ALEXANDER CITY ALTIMETER SETTING AND INCREASE ALL MDA 120 FEET AND INCREASE LNAV CAT A VISIBILITY 1/4 MILE, LNAV CAT C VISIBILITY 1/2 MILE, CIRCLING CAT A VISIBILITY 1/4 MILE AND CIRCLING CAT C VISIBILITY 1/2 MILE. THIS IS RNAV (GPS) RWY 9, ORIG-C. 1905291227-PERM