

**Federal Aviation
Administration**

Transmittal Letter 19-16

June 14, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	MI	Bad Axe	Huron County Memorial	9/0743	6/7/2019	RNAV (GPS) RWY 17, Orig-A

AIRAC Date: 18 July 2019

FDC 9/0743 BAX IAP HURON COUNTY MEMORIAL, Bad Axe, MI. RNAV (GPS) RWY 17, ORIG-A... CHART NOTE:
RWY 17 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. PBN REQUIREMENTS
NOTE: RNP APCH. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MBS INTL
ALTIMETER SETTING AND INCREASE ALL DA 129 FEET AND ALL MDA 140 FEET; INCREASE LPV ALL CATS
VISIBILITY 3/8 MILE; INCREASE LNAV CAT C 1/2 MILE. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV
SYSTEMS, LNAV/VNAV NA BELOW -16 C OR ABOVE 54 C. DELETE CIRCLING MINIMUMS. DELETE NOTE:
WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MBS INTL ALTIMETER SETTING AND INCREASE
ALL DA 129 FEET AND ALL MDA 140 FEET; INCREASE LPV ALL CATS VISIBILITY 3/8 MILE; INCREASE LNAV
CAT C AND CIRCLING CAT C VISIBILITY 1/2 MILE. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION
BELOW 1 SM NA. DELETE NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: FOR UNCOMPENSATED
BARO/VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130 F). THIS IS RNAV (GPS) RWY
17, ORIG-B. 1906061934-PERM