Federal Aviation Administration

Transmittal Letter 19-16

June 14, 2019

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/18/2019	MI	Bad Axe	Huron County Memorial	9/5426	6/3/2019	RNAV (GPS) RWY 22, Orig-B

AIRAC Date: 18 July 2019

FDC 9/5426 BAX IAP HURON COUNTY MEMORIAL, Bad Axe, MI. RNAV (GPS) RWY 22, ORIG-B... CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MBS INTL ALTIMETER SETTING AND INCREASE ALL MDA 140 FEET; INCREASE LNAV CAT C VISIBILITY 1/2 SM. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MBS INTL ALTIMETER SETTING AND INCREASE ALL MDA 140 FEET; INCREASE LNAV CAT C AND CIRCLING CAT C VISIBILITY 1/2 SM. DELETE CIRCLING MINIMUMS. THIS IS RNAV (GPS) RWY 22, ORIG-C. 1905291650-PERM