

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
DOGGE	JUGEB (FB)	176.41 / 17.91	2000	LNAV: RW09			
WORKS	OYUTI (FB)	020.35 / 12.83	2000				
JUGEB (IAF)	HITIB (NOPT) (FB)	177.50 / 5.00	2000	CLIMB TO 2000 DIRECT JIMIB AND HOLD.			
OYUTI (IAF)	HITIB (NOPT) (FB)	357.50 / 5.00	2000				
HITIB (IF/IAF)	ICEDA (FB)	087.50 / 6.04	1900	ADDITIONAL FLIGHT DATA: HOLD E, RT, 267.75 INBOUND. FAS OBST: 539 AAO 325115N/0940551W ICEDA TO RW09: 3.04/52.			

1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)	
2. HOLD W HITIB, RT, 087.50 INBOUND, 2000 FT. IN LIEU OF PT (IAF)	
3. FAC: 087.57 FAF: ICEDA DIST FAF TO MAP: 4.96 THLD: 4.96	
4. MIN. ALT: HITIB 2000, ICEDA 1900	
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____	
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____	
7. GS ANGLE: _____ TCH: 34:1 IS CLEAR	
8. MSA FROM: RW09 3100	

MINIMUMS	
TAKEOFF: ☐ STANDARD ☒ X SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A ☐ X ☐	
CATEGORY =====>	
	A B C D E
	DH/MDA VIS HAT/HAA DH/MDA VIS HAT/HAA DH/MDA VIS HAT/HAA DH/MDA VIS HAT/HAA DH/MDA VIS HAT/HAA
LNAV MDA	860 1 600 860 1 600 860 1 1/2 600 NA NA NA NA NA NA
CIRCLING	860 1 600 860 1 600 880 1 3/4 620 NA NA NA NA NA NA

NOTES:
 CHART NOTE: CIRCLING NA NORTH OF RWY 09/27.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: WHEN SHREVEPORT REGIONAL ALTIMETER SETTING NOT RECEIVED, USE SHREVEPORT DOWNTOWN ALTIMETER SETTING.

CITY AND STATE VIVIAN, LA	ELEVATION: 260 TDZE: 260 AIRPORT NAME: VIVIAN	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, ORIG 12 MAR 2009	SUP: AMDT: NONE DATED
----------------------------------	---	------------------------------	---	-----------------------------

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC PACKET - 424-18[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	3F4	K4FR09	ADOGGE	010DOGG	EK4EA0E	IF				18000		B	JS
SUSAP	3F4	K4FR09	ADOGGE	020JUGEB	K4EA0E	A 020TF	17640179	+ 02000				B	JS
SUSAP	3F4	K4FR09	ADOGGE	030HITIB	K4EA0EE	010TF	17750050	+ 02000				B	JS
SUSAP	3F4	K4FR09	AHITIB	010HITIB	K4EA0EE	CR HF	08750040	+ 02000		18000		B	JS
SUSAP	3F4	K4FR09	AWORKS	010WORKS	K4EA0E	IF				18000		B	JS
SUSAP	3F4	K4FR09	AWORKS	020OYUTI	K4EA0E	A 020TF	02040128	+ 02000				B	JS
SUSAP	3F4	K4FR09	AWORKS	030HITIB	K4EA0EE	010TF	35750050	+ 02000				B	JS
SUSAP	3F4	K4FR09	R	010HITIB	K4EA0E	I IF		+ 02000		18000		B	JS
SUSAP	3F4	K4FR09	R	020ICEDAK	4EA1E	F 051TF	08750060	+ 01900			RW09	K4PGB	JS
SUSAP	3F4	K4FR09	R	020ICEDAK	4EA2WN		N	ALNAV					JS
SUSAP	3F4	K4FR09	R	030RW09	K4PG0GY	M 031TF	08760050		00299	-304		B	JS
SUSAP	3F4	K4FR09	R	040JIMIBK	4EA0EYM	010DF		+ 02000				B	JS
SUSAP	3F4	K4FR09	R	050JIMIBK	4EA0EE	HR020HM	26780040	+ 02000				B	JS

[illegible]

1		2		3		4		5		6		7		8		9		0		1		2		3
---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---	--	---

CITY AND STATE

VIVIAN, LA

ELEVATION: 260 TDZE: 260

AIRPORT NAME:

VIVIAN

FACILITY
IDENTIFIER:
BNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 9, ORIG

12 MAR 2009

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

MSA 1234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP 3F4 K4SRW09 K4PG 0 18018003125 M

CITY AND STATE

VIVIAN, LA

ELEVATION: 260 TDZE: 260

AIRPORT NAME:

VIVIAN

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 9, ORIG

12 MAR 2009

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	DOGGE	DOGGE	010		IF		FB				
	DOGGE	JUGEB	020	IAF	TF		FB	2.0	176.4 (178T)	017.9	02000
	DOGGE	HITIB	030		TF		FB	1.0	177.5 (180T)	005.0	02000
	HITIB	HITIB	010		HF	R	FB		087.5 (090T)	004.0	02000
	WORKS	WORKS	010		IF		FB				
	WORKS	OYUTI	020	IAF	TF		FB	2.0	020.4 (022T)	012.8	02000
	WORKS	HITIB	030		TF		FB	1.0	357.5 (360T)	005.0	02000
		HITIB	010	FACF	IF		FB				02000
		ICEDA	020	FAF	TF		FB	0.5	087.5 (090T)	006.0	01900
		RW09	030	MAP	TF		FO	0.3	087.6 (090T)	005.0	00299

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	JIMIB	040		DF		FO	1.0			02000
	JIMIB	050		HM	R	FO	2.0	267.8 (270T)	004.0	02000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DOGGE	N331432.72	W0941436.23	N3314.545	W09414.604
	HITIB	N325135.63	W0941357.64	N3251.594	W09413.961
	ICEDA	N325138.58	W0940647.35	N3251.643	W09406.789
	JIMIB	N325144.48	W0934715.43	N3251.741	W09347.257
	JUGEB	N325636.21	W0941400.75	N3256.604	W09414.013
	OYUTI	N324635.05	W0941354.53	N3246.584	W09413.909
	WORKS	N323441.68	W0941941.75	N3234.695	W09419.696
	RW09	N325140.70	W0940054.12	N3251.678	W09400.902

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW09	00247	52

CITY AND STATE VIVIAN, LA	ELEVATION: 260	TDZE: 260	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, ORIG 12 MAR 2009	SUP:
	AIRPORT NAME: VIVIAN				AMDT: NONE
					DATED: