

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH								
FROM	TO	COURSE AND DISTANCE	ALTITUDE									
GOVVE (IF) (40E) (43I)	COTBA/6.10 NM TO JODIP (TF) (FB) (40E) (42S)	032.53 / 6.40	7000	LNAV: ODACE								
COTBA (40E) (42S)	JODIP (TF) (FB) (40E) (43F)	032.53 / 6.10	5100									
ODACE (MAP) (40E) (41Y) (43M)	2854 MSL (CA) (42M)	046.64		CLIMB TO 9000 DIRECT HETOM AND VIA 333.44 TRACK TO BACRA AND HOLD, CONTINUE CLIMB-IN-HOLD TO 9000.								
2854 MSL	HETOM (DF) (FB) (40E)											
HETOM (40E)	BACRA (TF)(FO)(40E)(41E)(43H)	333.44 / 13.94	9000	ADDITIONAL FLIGHT DATA: HOLD S, LT, 360.00 INBOUND FAS OBST: 3199 TREE 350552N/1181104W FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD JODIP TO RW06: 3.06/50 ROUTE TYPE DESCRIPTION: A,P APPROACH ROUTE QUALIFIER 2: S CHART: MIRL RWY 06/24 CHART: R-2515, R-2506, ISABELLA MOA, BAKERSFIELD MOA								
1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)				MAG VAR: 14E EPOCH YEAR: 05								
2. PROFILE STARTS AT GOVVE												
3. FAC: 046.64 FAF: JODIP DIST FAF TO MAP: 7.52 THLD: 8.00												
4. MIN. ALT: GOVVE 9000, COTBA 7000, JODIP 5100												
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:												
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:												
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR												
8. MSA FROM: ODACE 9800												
MINIMUMS												
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X							
CATEGORY =====>	A		B		C		D		E			
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	3660	1 1/4	1206	3660	1 1/2	1206	3660	3	1206	NA		
CIRCLING	3660	1 1/4	1206	3660	1 1/2	1206	3660	3	1206	NA		
NOTES: CHART NOTES: DME/DME RNP-0.3 NA. IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE EDWARDS AFB ALTIMETER SETTING AND INCREASE ALL MDAs 60 FEET; IF NEITHER RECEIVED, PROCEDURE NA. PROCEDURE NA AT NIGHT. CHART PLANVIEW NOTE: RADAR REQUIRED.												
CITY AND STATE		ELEVATION: 2454 TDZE: 2454		FACILITY IDENTIFIER:		PROCEDURE NO. /AMDT NO. /EFFECTIVE DATE:		SUP:				
CALIFORNIA CITY, CA		CALIFORNIA CITY MUNI		RNAV		MAR 17 2005 RNAV (GPS) RWY 6, ORIG		AMDT: NONE				
								DATE				