

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW07
SAPPE	KEBTY (FB)	062.48 / 12.74	3000	CLIMB TO 3000 DIRECT EDEJU AND HOLD.
NOLLI	EBBIL (FB)	170.61 / 14.81	3000	
RAZZR	EBBIL (FB)	241.09 / 25.60	3000	
EBBIL (IAF)	BAZQE (FB)	159.52 / 5.00	2400	
KEBTY (IAF)	BAZQE (FB)	339.62 / 5.00	2400	
BAZQE (IF)	AVOIL (FB)	069.57 / 6.17	1700	
				ADDITIONAL FLIGHT DATA: HOLD E, RT, 249.85 INBOUND. CHART FAS OBST: 279 TREE 435632N/0694514W CHART 412 CRANE 435429N/0694850W. AVOIL TO RW07: 3.04/40.

1. PT NA SIDE OF COURSE          OUTBOUND          FT WITHIN          MILES OF          (IAF)
2. PROFILE STARTS AT BAZQE
3. FAC: 069.65 FAF: AVOIL DIST FAF TO MAP: 4.93 THLD: 4.93
4. MIN. ALT: BAZQE 2400, AVOIL 1700 /
5. DIST TO THLD FROM OM:          MM:          IM:          150 HAT:          100 HAT:          GS ANT:
6. MIN GS INCPT:          GS ALT AT:          OM:          MM:          IM:
7. GS ANGLE:          TCH: 34:1 IS NOT CLEAR
8. MSA FROM: RW07 2600

MAG VAR: 18W EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N/A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	560	1	490	560	1	490		NA			NA				
CIRCLING	640	1	570	640	1	570		NA			NA				

NOTES:  
 CHART NOTE: DME/DME RNP-0.3 NA.  
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.  
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED USE ROCKLAND ALTIMETER SETTING AND INCREASE  
 SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY  
5  
CHECKED

CITY AND STATE <b>WISCASSET, ME</b>	ELEVATION: 70 TDZE: 70 AIRPORT NAME: <b>WISCASSET</b>	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG <b>03 JUN 2010</b>	SUP: AMDT: NONE DATED
--	---	------------------------------	--	-----------------------------

**RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES CONT.**

**ALL MDA 80 FEET.**

**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL AT SAPPE VIA V268 SOUTH BOUND AND AT RAZZR VIA V93 NORTHEAST BOUND.**

**CHART NOTE: CIRCLING NA SE OF RWY 7-25.**



CITY AND STATE <b>WISCASSET, ME</b>	ELEVATION: 70 TDZE: 70 AIRPORT NAME: <b>WISCASSET</b>	FACILITY IDENTIFIER: <b>RNAV</b>	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: <b>RNAV (GPS) RWY 7, ORIG</b>  <b>03 JUN 2010</b>	SUP:
				AMDT: <b>NONE</b>
				DATED:



