

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW03 CLIMB TO 2400 DIRECT GUNKE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 209.75 INBOUND. CHART FAS OBST: 716 TOWER 332422N/0894603W RASME TO RW03: 3.00/30. CHART GRENADA AWOS											
GUCEY (IF/IAF) RASME (FAF) RW03 (MAP) 764 MSL	RASME (FB) RW03 (MAP) (FO) 764 MSL GUNKE (FO)	029.62 / 6.00 029.65 / 5.09 029.65	2000 2400												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW GUCEY, RT, 029.62 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC: <u>029.65</u> FAF: <u>RASME</u> DIST FAF TO MAP: <u>5.09</u> THLD: <u>5.09</u> 4. MIN. ALT: <u>GUCEY 2500, RASME 2000</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1</u> IS NOT CLEAR 8. MSA FROM: <u> </u>															
				MAG VAR: 1W EPOCH YEAR: 2010											
MINIMUMS															
TAKEOFF: <u>SEE FAA FORM 8260-15A FOR THIS AIRPORT</u>			ALTERNATE: <u>N A</u> ☒ <u>X</u>												
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1040	1	692	1040	1	692	1040	2	692		NA				
CIRCLING	1040	1	676	1040	1	676	1040	2	676		NA				
NOTES: CHART NOTE: USE GRENADA ALTIMETER SETTING; WHEN NOT RECEIVED, USE GREENWOOD ALTIMETER SETTING. CHART NOTE: CIRCLING NA NW OF RWY 3-21. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)															
CITY AND STATE WINONA, MS		ELEVATION: 364 THR: 348 AIRPORT NAME: WINONA-MONTGOMERY COUNTY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 10 JANUARY 2013				SUP: AMDT: ORIG DATED 02/14/2008					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSi AND DESCENT ANGLES NOT COINCIDENT.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	300/30 CW 120/30 (NOPT)	GUCEY (IF/IAF) (FB)	2500
2.	120/30 CW 300/30	GUCEY (IF/IAF) (FO)	2500

CITY AND STATE

WINONA, MS

ELEVATION: 364

THRE: 348

AIRPORT NAME:

WINONA-MONTGOMERY COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 3, AMDT 1

10 JANUARY 2013

SUP:

AMDT: ORIG

DATED: 02/14/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibility which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 5A6 K7FR03	AGUCEY	010GUCEYK7EA0EE	AR	HF		02960040	+	02500	18000			B	JS
SUSAP 5A6 K7FR03	R	010GUCEYK7EA0E	I	IF			+	02500	18000			B	JS
SUSAP 5A6 K7FR03	R	020RASMEK7EA1E	F	051TF		02960060	+	02000				B	JS
SUSAP 5A6 K7FR03	R	020RASMEK7EA2WN			N	ALNAV							JS
SUSAP 5A6 K7FR03	R	030RW03 K7PGOGY	M	031TF		02970051		00378		-300		B	JS
SUSAP 5A6 K7FR03	R	040	0	M	CA	0297	+	00764				B	JS
SUSAP 5A6 K7FR03	R	050GUNKEK7EA0EY		DF			+	02400				B	JS
SUSAP 5A6 K7FR03	R	060GUNKEK7EA0EE	R	HM		20980040	+	02400				B	JS

[illegible]

CITY AND STATE WINONA, MS	ELEVATION: 364 THRE: 348 AIRPORT NAME: WINONA-MONTGOMERY COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 10 JANUARY 2013	SUP:
				AMDT: ORIG
				DATED: 02/14/2008

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	GUCEY	GUCEY	010	IAF	HF	R	FO		029.6 (028.6T)	004.0	AA 02500	
		GUCEY	010	FACF	IF		FB				AA 02500	
		RASME	020	FAF	TF		FB	0.5	029.6 (028.6T)	006.0	AA 02000	
		RW03	030	MAP	TF		FO	0.3	029.7 (028.7T)	005.1	AT 00378	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		029.7 (028.7T)		AA 00764	
	GUNKE	050		DF		FO				AA 02400	
	GUNKE	060		HM	R	FO		209.8 (208.8T)	004.0	AA 02400	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	GUCEY	N331751.31	W0895021.27	N3317.855	W08950.355
	GUNKE	N333810.05	W0893705.62	N3338.168	W08937.094
	RASME	N332307.87	W0894655.32	N3323.131	W08946.922
	RW03	N332736.60	W0894400.11	N3327.610	W08944.002

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW03	00348	30

CITY AND STATE
WINONA, MS

ELEVATION: 364 THRE: 348
 AIRPORT NAME:
 WINONA-MONTGOMERY COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
 RNAV (GPS) RWY 3, AMDT 1
 10 JANUARY 2013

SUP:
 AMDT: ORIG
 DATED: 02/14/2008