

**Federal Aviation
Administration**

Transmittal Letter 19-24

October 4, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/7/2019	TX	Brenham	Brenham Muni	9/5736	9/18/2019	RNAV (GPS) RWY 16, Amdt 2B

AIRAC Date: 7 NOVEMBER 2019

FDC 9/5736 11R IAP BRENHAM MUNI, Brenham, TX. RNAV (GPS) RWY 16, AMDT 2B... DELETE CIRCLING MINIMUMS. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: RWY 16 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NA. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 37C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 37C (98F). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLLEGE STATION ALTIMETER SETTING AND INCREASE ALL DA 52 FEET, AND ALL MDA 60 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS AND LNAV CAT C/D VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE COLLEGE STATION ALTIMETER SETTING AND INCREASE ALL DA 52 FEET, AND ALL MDA 60 FEET. INCREASE LPV AND LNAV/VNAV ALL CATS, LNAV CATS C/D AND CIRCLING CATS C/D VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) RWY 16, AMDT 2C. 1909091607-PERM