

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW17 CLIMB TO 3500 DIRECT CUDVI AND VIA 111.56 TRACK TO NUMMO AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3500. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 307.80 INBOUND. CHART FAS OBST: 964 TOWER 294459N/0980306W CHART VDP AT 1.64 MILES TO RW17. RAZVY TO RW17: 3.03/45. CHART A-638 CHART PLANVIEW: RANDOLF AFB AUX (KSEQ)	
SHEPE (IAF)	ACGET (FB)	071.81 / 5.90	3100		
ACGET (IF)	EKKOP (FB)	147.73 / 3.05	2600		
EKKOP	RAZVY (FB)	147.73 / 3.00	2000		
1. PT <u>NA</u> SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT ACGET 3. FAC: <u>172.72</u> FAF: <u>RAZVY</u> DIST FAF TO MAP: <u>4.06</u> THLD: <u>4.06</u> 4. MIN. ALT: <u>ACGET 3100, EKKOP 2600, RAZVY 2000</u> 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: <u>34:1</u> IS CLEAR 8. MSA FROM: <u>RW17 3100</u>				MAG VAR: <u>8E</u> EPOCH YEAR: <u>1975</u>	
MINIMUMS					
TAKEOFF:	☐ STANDARD	☒ X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: <u>NA</u>	STANDARD ©
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	1220	1	569	1220	1
CIRCLING	1220	1	569	1280	1 3/4
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 1/2	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA
	1220	1 3/4	569	1220	1 3/4
	569	629	1280	2	629
	HAT/HAA	DH/MDA	VIS		

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE NEW BRAUNFELS, TX	ELEVATION: 651 TDZE: 651 AIRPORT NAME: NEW BRAUNFELS MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG FEB 14 2008	SUP: AMDT: NONE DATED:
-------------------------------------	---	---------------------------------	--	------------------------------

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

3 of 4

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-15

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	SHEPE	SHEPE	010	IAF	IF		FB				
	SHEPE	ACGET	020		TF		FB	1.0	071.8 (080T)	005.9	03100
		ACGET	010	FACF	IF		FB				03100
		EKKOP	020	SDF	TF		FB	0.5	147.7 (156T)	003.1	02600
		RAZVY	021	FAF	TF		FB	0.5	147.7 (156T)	003.0	02000
		RW17	030	MAP	TF		FO	0.3	172.7 (181T)	004.1	00693

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
		040		CA		FB	1.0	172.7 (181T)		01051
	CUDVI	050		DF		FB	1.0			
	NUMMO	060		TF		FO	1.0	111.6 (120T)		03500
	NUMMO	070		HM	R	FO	2.0	307.8 (316T)	004.0	03500

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ACGET	N295204.78	W0980525.07	N2952.080	W09805.418
	CUDVI	N293901.09	W0980240.14	N2939.018	W09802.669
	EKKOP	N294917.61	W0980358.62	N2949.294	W09803.977
	NUMMO	N293434.04	W0975342.01	N2934.567	W09753.700
	RAZVY	N294633.10	W0980233.63	N2946.552	W09802.561
	SHEPE	N295102.19	W0981205.65	N2951.037	W09812.094
	RW17	N294229.20	W0980237.14	N2942.487	W09802.619

RUNWAY DATA	THRESHOLD	
RWY	ELEVATION	TCH
RW17	00648	45

CITY AND STATE NEW BRAUNFELS, TX	ELEVATION: 651 TDZE: 651	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, ORIG FEB 14 2008	SUP:
	AIRPORT NAME: NEW BRAUNFELS MUNI			AMDT: NONE
				DATED: