

**Federal Aviation
Administration**

Transmittal Letter 19-17

June 28, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/15/2019	NC	Shelby	Shelby-Cleveland County Rgnl	9/0828	6/25/2019	RNAV (GPS) RWY 23, Orig-A

AIRAC Date: 15 AUGUST 2019

FDC 9/0828 EHO IAP SHELBY-CLEVELAND COUNTY RGNL, Shelby, NC. RNAV (GPS) RWY 23, ORIG-A...
DELETE CIRCLING MINIMUMS. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 38C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 38C (100F). PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLOTTE ALTIMETER SETTING AND INCREASE ALL DA 88 FEET AND ALL MDA 100 FEET; INCREASE LPV ALL CATS VISIBILITY 1/8 SM AND LNAV/VNAV ALL CATS, LNAV CAT C/D VISIBILITY 1/4 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CHARLOTTE ALTIMETER SETTING AND INCREASE ALL DA 88 FEET AND ALL MDA 100 FEET; INCREASE LPV ALL CATS VISIBILITY 1/8 MILE AND LNAV/VNAV ALL CATS, LNAV CAT C/D AND CIRCLING CAT D VISIBILITY 1/4 MILE. DELETE NOTE: WHEN VGSI INOP, CIRCLING RWY 5 NA AT NIGHT. DELETE NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 23 PROCEDURE NA AT NIGHT. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. THIS IS RNAV (GPS) RWY 23, ORIG-B. 1906241319-PERM