

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION	RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	---	--

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
RUSIF (IAF)	MUCRO (NOPT) (FB)	119.98 / 5.00	2000	LNAV: RW03 CLIMB TO 2000 DIRECT COJLA AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 210.12 INBOUND. CHART FAS OBST: 226 TOWER 282746N/0822642W CHART 309 TOWER 282401N/0822852W. OFKOR TO RW03: 3.05/45
CUNJU (IAF)	MUCRO (NOPT) (FB)	300.06 / 5.00	2000	
MUCRO (IF/IAF)	OFKOR (FB)	030.02 / 6.20	1800	

1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)	
2. HOLD SW MUCRO, LT, 030.02 INBOUND, 2000 FT. IN LIEU OF PT (IAF)	
3. FAC: 030.05 FAF: OFKOR	DIST FAF TO MAP: 5.22 THLD: 5.22
4. MIN. ALT: MUCRO 2000, OFKOR 1800, FOREK/2.50 NM TO RW03 900	
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____	150 HAT: _____ 100 HAT: _____ GS ANT: _____
6. MIN GS INCPT: _____ GS ALT AT: _____	OM: _____ MM: _____ IM: _____
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR	
8. MSA FROM: _____	

MAG VAR: 4W EPOCH YEAR: 2000

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	480	1	413	480	1	413	480	1 1/4	413	480	1 1/4	413			
CIRCLING	540	1	464	540	1	464	540	1 1/2	464	640	2	564			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TAMPA INTL ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND INCREASE LNAV CAT D VISIBILITY 1/4 MILE.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE BROOKSVILLE, FL	ELEVATION: 76 TDZE: 67 AIRPORT NAME: HERNANDO COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 02 JUL 2009	SUP: AMDT: ORIG DATED 09/04/2003
-----------------------------------	--	------------------------------	---	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	300/30 CW 120/30 (NOPT)	300/10 CW 120/10	3000
	300/10 CW 120/10	MUCRO (IF/IAF) (FB)	2000
2.	120/30 CW 210/30	RUSIF (IAF) (FB)	2000
3.	210/30 CW 300/30	CUNJU (IAF) (FB)	2000

QUALITY
1
CHECKED

CITY AND STATE
BROOKSVILLE, FL

ELEVATION: 76 TDZE: 67
AIRPORT NAME:
HERNANDO COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 3, AMDT 1
02 JUL 2009

SUP:
AMDT: ORIG
DATED: 09/04/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE BROOKSVILLE, FL	ELEVATION: 76 TDZE: 67 AIRPORT NAME: HERNANDO COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 3, AMDT 1 02 JUL 2009	SUP:
				AMDT: ORIG
				DATED: 09/04/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	CUNJU	CUNJU	010	IAF	IF		FB				
	CUNJU	MUCRO	020		TF		FB	1.0	300.1 (296T)	005.0	02000
	MUCRO	MUCRO	010		HF	L	FB		030.0 (026T)	004.0	02000
	RUSIF	RUSIF	010	IAF	IF		FB				
	RUSIF	MUCRO	020		TF		FB	1.0	120.0 (116T)	005.0	02000
		MUCRO	010	FACF	IF		FB				02000
		OPKOR	020	FAF	TF		FB	0.5	030.0 (026T)	006.2	01800
		FOREK	021	SDF	TF		FB	0.3	030.1 (026T)	002.7	0090000928
		RW03	030	MAP	TF		FO	0.3	030.1 (026T)	002.5	00112

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	COJLA	040		DF		FO	1.0			02000
	COJLA	050		HM	R	FO	2.0	210.1 (206T)	004.0	02000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	COJLA	N283852.40	W0822103.19	N2838.873	W08221.053
	CUNJU	N281521.63	W0822746.21	N2815.361	W08227.770
	FOREK	N282535.76	W0822825.04	N2825.596	W08228.417
	MUCRO	N281733.63	W0823251.37	N2817.561	W08232.856
	OPKOR	N282308.56	W0822946.43	N2823.143	W08229.774
	RUSIF	N281945.44	W0823756.74	N2819.757	W08237.946
	RW03	N282750.87	W0822710.26	N2827.848	W08227.171

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW03	00067	45

CITY AND STATE
BROOKSVILLE, FL

ELEVATION: 76 TDZE: 67
 AIRPORT NAME:
 HERNANDO COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 3, AMDT 1
 02 JUL 2009

SUP:
 AMDT: ORIG
 DATED: 09/04/2003