

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV (GPS) - STANDARD INSTRUMENT APPROACH PROCEDURE FAR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW21 CLIMB TO 2000 DIRECT MUCRO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, LT, 030.02 INBOUND. CHART FAS OBST: 230 TOWER 283018N/0822513W CHART 432 TOWER 283246N/0822251W. HINQE TO RW21: 3.05/45	
EPNIF (IAF)	COJLA (NOPT) (FB)	300.16 / 5.00	2000		
LEVSE (IAF)	COJLA (NOPT) (FB)	120.08 / 5.00	2000		
COJLA (IF/IAF)	HINQE (FB)	210.12 / 6.20	1800		
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NE COJLA, RT, 210.12 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>210.10</u> FAF: <u>HINQE</u> DIST FAF TO MAP: <u>5.22</u> THLD: <u>5.22</u> 4. MIN. ALT: <u>COJLA 2000, HINQE 1800, CEGIM/2.50 NM TO RW21 900</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1 IS NOT CLEAR</u> 8. MSA FROM: <u> </u>					
				MAG VAR: 4W EPOCH YEAR: 2000	
MINIMUMS					
TAKEOFF: <u> </u>	☐ STANDARD	☒ X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
LNAV MDA	480	1	411	480	1 1/4
CIRCLING	540	1	464	540	1 1/2
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TAMPA INTL ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND INCREASE LNAV CAT D VISIBILITY 1/4 MILE.					
CITY AND STATE BROOKSVILLE, FL		ELEVATION: 76 TDZE: 69 AIRPORT NAME: HERNANDO COUNTY		FACILITY IDENTIFIER: RNAV PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, AMDT 1 02 JUL 2009	
				SUP: AMDT: ORIG DATED 09/04/2003	

 QUALITY
1
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	120/30 CW 300/30 (NOPT)	COJLA (IF/IAF) (FB)	2000
2.	300/30 CW 030/30	EPNIF (IAF) (FB)	2000
3.	030/30 CW 120/30	LEVSE (IAF) (FB)	2000

QUALITY
1
CHECKED

CITY AND STATE
BROOKSVILLE, FL

ELEVATION: 76 TDZE: 69
AIRPORT NAME:
HERNANDO COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 21, AMDT 1
02 JUL 2009

SUP:
AMDT: ORIG
DATED: 09/04/2003

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE BROOKSVILLE, FL	ELEVATION: 76 TDZE: 69 AIRPORT NAME: HERNANDO COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, AMDT 1 02 JUL 2009	SUP:
				AMDT: ORIG
				DATED: 09/04/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/PB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	COJLA	COJLA	010		HF	R	FB		210.1 (206T)	004.0	02000
	EPNIF	EPNIF	010	IAP	IF		FB				
	EPNIF	COJLA	020		TF		FB	1.0	300.2 (296T)	005.0	02000
	LEVSE	LEVSE	010	IAP	IF		FB				
	LEVSE	COJLA	020		TF		FB	1.0	120.1 (116T)	005.0	02000
		COJLA	010	FACF	IF		FB				02000
		HINQE	020	PAF	TF		FB	0.5	210.1 (206T)	006.2	01800
		CEGIM	021	SDF	TF		FB	0.3	210.1 (206T)	002.7	0090000928
		RW21	030	MAP	TF		FO	0.3	210.1 (206T)	002.5	00113

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/PB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	MUCRO	040		DF		FO	1.0			02000
	MUCRO	050		HM	L	FO	2.0	030.0 (026T)	004.0	02000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	CEGIM	N283050.56	W0822530.74	N2830.843	W08225.512
	COJLA	N283852.40	W0822103.19	N2838.873	W08221.053
	EPNIF	N283639.88	W0821557.15	N2836.665	W08215.953
	HINQE	N283317.65	W0822409.11	N2833.294	W08224.152
	LEVSE	N284104.72	W0822609.45	N2841.079	W08226.158
	MUCRO	N281733.63	W0823251.37	N2817.561	W08232.856
	RW21	N282835.47	W0822645.56	N2828.591	W08226.759

RUNWAY DATA	THRESHOLD	
RWY	ELEVATION	TCH
RW21	00068	45

QUALITY
1
CHECKED

CITY AND STATE BROOKSVILLE, FL	ELEVATION: 76 TDZE: 69	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, AMDT 1 02 JUL 2009	SUP:
	AIRPORT NAME: HERNANDO COUNTY			AMDT: ORIG
				DATED: 09/04/2003