

**Federal Aviation
Administration**

Transmittal Letter 19-24

October 4, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/7/2019	FL	Bartow	Bartow Executive	9/1040	9/20/2019	RNAV (GPS) RWY 23, Orig-C

AIRAC Date: 7 NOVEMBER 2019

FDC 9/1040 BOW IAP BARTOW EXECUTIVE, Bartow, FL. RNAV (GPS) RWY 23, ORIG-C... DELETE CIRCLING MINIMUMS. CHART NOTE: RWY 23 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: RWY 5 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TAMPA INTL ALTIMETER SETTING AND INCREASE LPV DA TO 560 FT, LNAV/VNAV DA TO 681 FT AND ALL MDA 120 FT, INCREASE LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS 1/8 SM, LNAV CAT C 1/4 SM, CAT D 1/8 SM AND CIRCLING CAT C 1/8 SM, CAT D 1/4 SM. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TAMPA INTL ALTIMETER SETTING AND INCREASE LPV DA TO 560 FT, LNAV/VNAV DA TO 681 FT AND ALL MDA 120 FT, INCREASE LPV ALL CATS VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS 1/8 SM, LNAV CAT C 1/4 SM, CAT D 1/8 SM. DELETE NOTE: CIRCLING RWY 9L, 27L NA AT NIGHT. THIS IS RNAV (GPS) RWY 23, ORIG-D. 1909171658-PERM