

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LNAV: RW23						
RBV VORTAC		COBUS (FB)		250.87 / 16.95			2000		CLIMBING RIGHT TURN TO 2000 DIRECT HOLEY AND HOLD.						
ARD VOR/DME		COBUS (FB)		171.18 / 12.67			2000								
COBUS (IAF)		HOLEY (FB)		200.81 / 5.11			2000								
HOLEY (IF)		MUNGY (FB)		209.67 / 7.84			1800								
MUNGY (FAF)		RW23 (MAP) (FO)		230.01 / 5.00			2000								
RW23 (MAP)		550 MSL		230.01					ADDITIONAL FLIGHT DATA: HOLD N, RT, 200.81 INBOUND. CHART FAS OBST: 500 TOWER 394743N/0745546W						
550 MSL		HOLEY (FO)													
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 12W EPOCH YEAR: 2000					
2. PROFILE STARTS AT HOLEY															
3. FAC: 230.01 FAF: MUNGY DIST FAF TO MAP: 5.00 THLD: 5.00															
4. MIN. ALT: HOLEY 2000, MUNGY 1800															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR															
8. MSA FROM: RW23 2600															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		X									
CATEGORY ==>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	840	1	698	840	1	698		NA			NA				
CIRCLING	900	1	750	900	1	750		NA			NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: USE MOUNT HOLLY ALTIMETER SETTING; WHEN NOT RECEIVED, USE PHILADELPHIA INTL ALTIMETER (CONTINUED ON PAGE 2)															
CITY AND STATE BERLIN, NJ		ELEVATION: 150 TDZE: 142 AIRPORT NAME: CAMDEN COUNTY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 23, ORIG-B 3 MARCH 2016				SUP: 4		AMDT: ORIG-A		DATED 01/12/2012	

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

SETTING AND INCREASE ALL MDA 20 FEET.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RBV VORTAC ON AIRWAY RADIALS 238 CW 289.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ARD VOR/DME ON V479 NORTHBOUND.

CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.

CITY AND STATE

BERLIN, NJ

ELEVATION: 150

TDZE: 142

AIRPORT NAME:

CAMDEN COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 23, ORIG-B
3 MARCH 2016

SUP:

4

AMDT:

ORIG-A

DATED:

01/12/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 19N

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
ARD	010	ARD	IF	FB										V
ARD	020	COBUS	TF	FB	2.0	171.2						AA 02000		E A
ARD	030	HOLEY	TF	FB	1.0	200.8						AA 02000		EE B
RBV	010	RBV	IF	FB										V
RBV	020	COBUS	TF	FB	2.0	250.9						AA 02000		E A
RBV	030	HOLEY	TF	FB	1.0	200.8						AA 02000		EE B
	010	HOLEY	IF	FB								AA 02000		E I
	020	MUNGY	TF	FB	0.5	209.7				RW23		AA 01800		E F
	030	RW23	TF	FO	0.3	230.0		3.05				AT 00180		GY M
	040		CA	FB		230.0						AA 00550		M
	050	HOLEY	DF	FO					R			AA 02000		EY
	060	HOLEY	HM	FO		200.8			R			AA 02000		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
ARD	N401512.03	W0745427.40
RBV	N401208.65	W0742942.09
COBUS	N400321.00	W0744835.69
HOLEY	N395817.71	W0744936.76
MUNGY	N395049.17	W0745242.14

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW23	N394652.56	W0745641.78	00140	40

CITY AND STATE BERLIN, NJ	ELEVATION: 150 TDZE: 142	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 23, ORIG-B 3 MARCH 2016	SUP: 4
	AIRPORT NAME: CAMDEN COUNTY			AMDT: ORIG-B
				DATED: 01/12/2012