

**Federal Aviation
Administration**

Transmittal Letter 19-18

July 12, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/15/2019	OK	Chandler	Chandler Rgnl	9/0910	6/28/2019	RNAV (GPS) RWY 35, Orig-A

AIRAC Date: 15 AUGUST 2019

FDC 9/0910 CQB IAP CHANDLER RGNL, Chandler, OK. RNAV (GPS) RWY 35, ORIG-A... DELETE CIRCLING MINIMUMS. DELETE NOTE: GPS OR RNP-0.3 REQUIRED. DELETE NOTE: BARO-VNAV NA BELOW -16C (4F). CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SHAWNEE ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET; INCREASE LNAV CAT C VISIBILITY 1/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SHAWNEE ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET; INCREASE LNAV CAT C VISIBILITY 1/8 MILE AND CIRCLING CAT C VISIBILITY 1/4 MILE. MISSED APPROACH: CLIMB TO 2600 DIRECT CADUT AND HOLD. THIS IS RNAV (GPS) RWY 35, ORIG-B. 1906241403-PERM