Federal Aviation Administration

Transmittal Letter 19-18

July 12, 2019

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/15/2019	NY	Hudson	Columbia County	9/0906	6/28/2019	RNAV (GPS) RWY 3, Orig-B

AIRAC Date: 15 AUGUST 2019

FDC 9/0906 1B1 IAP COLUMBIA COUNTY, Hudson, NY. RNAV (GPS) RWY 3, ORIG-B... DELETE CIRCLING MINIMUMS. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: RWY 3 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ALBANY ALTIMETER SETTING AND INCREASE ALL DA 76FT AND MDA 80FT, INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS, LNAV CATS C/D VISIBILITY 1/4 MILE. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ALBANY ALTIMETER SETTING AND INCREASE ALL DA 76FT AND MDA 80FT, INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS, LNAV CATS C AND D, AND CIRCLING CAT D VISIBILITY 1/4 MILE, AND CIRCLING CAT C VISIBILITY 1/2 MILE. THIS IS RNAV (GPS) RWY 3, ORIG-C. 1906241402-PERM