

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LP: RW17 LNAV: RW17 CLIMBING RIGHT TURN TO 3000 DIRECT JSSIE AND HOLD. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1019 TREE 414245N/0734333W CHART FAS OBST: 899 TREE 414354N/0734537W CHART NEWBURGH ATIS. WAAS CHANNEL # 78008 REFERENCE PATH ID: W17A KMBER TO RW17: 3.00/40. LTP HAE: 165.8 M											
WEETS	AROME (FB)	099.18 / 5.40	4000												
STUBY	GELAW (FB)	297.77 / 11.11	4000												
AROME (IAF)	JSSIE (NOPT) (FB)	099.54 / 10.01	3000												
GELAW (IAF)	JSSIE (NOPT) (FB)	256.74 / 8.91	3000												
JSSIE (IF/IAF)	KMBER (FB)	166.76 / 6.10	2300												
KMBER (FAF)	RW17 (MAP) (FO)	166.81 / 5.07													
RW17 (MAP)	1098 MSL	166.81													
1098 MSL	JSSIE (FO)		3000												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD N JSSIE, RT, 166.76 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>166.81</u> FAF: <u>KMBER</u> DIST FAF TO MAP: <u>5.07</u> THLD: <u>5.07</u> 4. MIN. ALT: JSSIE 3000, KMBER 2300 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW17 4500				MAG VAR: 14W EPOCH YEAR: 2000											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1240	1	594	1240	1	594		NA			NA				
LNAV MDA	1360	1	714	1360	1	714		NA			NA				
CIRCLING	1600	1 1/4	902	1600	1 1/4	902		NA			NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GELAW ON V44 NORTHBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WEETS ON V34-106 AND V483 NORTHWEST BOUND AND (SEE FORM 8260-10)															
CITY AND STATE MILLBROOK, NY				ELEVATION: 698 THRE: 646 AIRPORT NAME: SKY ACRES		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 2 20 SEPTEMBER 2012				SUP: AMDT: 1A DATED 11/18/2010			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

V213 SOUTHWEST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT STUBY ON V91-487 SOUTHBOUND AND V93 NORTHEAST BOUND.

CHART NOTE: USE NEWBURGH ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA.

QUALITY
2
CHECKED

CITY AND STATE MILLBROOK, NY	ELEVATION: 698	THRE: 646	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 2 20 SEPTEMBER 2012	SUP:
	AIRPORT NAME:				AMDT: 1A
	SKY ACRES				DATED: 11/18/2010

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER 44N
RUNWAY RW17
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W17A
LTP/FTP LATITUDE 414243.5590N
LTP/FTP LONGITUDE 0734428.4025W
LTP/FTP ELLIPSOIDAL HEIGHT +01658
FPAP LATITUDE 414124.2400N
FPAP LONGITUDE 0734334.1100W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1584
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 0.0

CRC REMAINDER

55F81A59

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +01970
FPAP ORTHOMETRIC HEIGHT +01970

QUALITY
2
CHECKED

CITY AND STATE
MILLBROOK, NY

ELEVATION: 698 THRE: 646
AIRPORT NAME:
SKY ACRES

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 17, AMDT 2
20 SEPTEMBER 2012

SUP:
AMDT: 1A
DATED: 11/18/2010

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 44N K6FR17	AJSSIE	010JSSIEK6EA0EE	AR	HF			16680040		+ 03000	18000		A JS	
SUSAP 44N K6FR17	ASTUBY	010STUBYK6EA0E		IF						18000		A JS	
SUSAP 44N K6FR17	ASTUBY	020GELAWK6EA0E	A	020TF			29780111		+ 04000			A JS	
SUSAP 44N K6FR17	ASTUBY	030JSSIEK6EA0EE	B	010TF			25670089		+ 03000			A JS	
SUSAP 44N K6FR17	AWEETS	010WEETSK6EA0E		IF						18000		A JS	
SUSAP 44N K6FR17	AWEETS	020AROMEK6EA0E	A	020TF			09920054		+ 04000			A JS	
SUSAP 44N K6FR17	AWEETS	030JSSIEK6EA0EE	B	010TF			09950100		+ 03000			A JS	
SUSAP 44N K6FR17	R	010JSSIEK6EA0E	I	IF					+ 03000	18000		A JS	
SUSAP 44N K6FR17	R	020KMBERK6EA1E	F	051TF			16680061		+ 02300		RW17	K6PGA	JS
SUSAP 44N K6FR17	R	020KMBERK6EA2WALP			N	ALNAV							JS
SUSAP 44N K6FR17	R	030RW17	K6PGGY	M	031TF		16680051		00686		-300		A JS
SUSAP 44N K6FR17	R	040		M	CA		1668		+ 01098				A JS
SUSAP 44N K6FR17	R	050JSSIEK6EA0EY	R	DF					+ 03000				A JS
SUSAP 44N K6FR17	R	060JSSIEK6EA0EE	R	HM			16680040		+ 03000				A JS

[illegible][illegible]

CITY AND STATE MILLBROOK, NY	ELEVATION: 698 AIRPORT NAME: SKY ACRES	THRE: 646 RNAV	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 2 20 SEPTEMBER 2012	SUP:
					AMDT: 1A
					DATED: 11/18/2010

FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
2
CHECKED

CITY AND STATE MILLBROOK, NY	ELEVATION: 698 AIRPORT NAME: SKY ACRES	THRE: 646 RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 17, AMDT 2 20 SEPTEMBER 2012	SUP:
				AMDT: 1A
				DATED: 11/18/2010

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	JSSIE	JSSIE	010	IAF	HF	R	FO		166.8(152.8T)	004.0	AA 03000	
	STUBY	STUBY	010		IF		FB					
	STUBY	GELAW	020	IAF	TF		FB	2.0	297.8(283.8T)	011.1	AA 04000	
	STUBY	JSSIE	030		TF		FB	1.0	256.7(242.7T)	008.9	AA 03000	
	WEETS	WEETS	010		IF		FB					
	WEETS	AROME	020	IAF	TF		FB	2.0	099.2(085.2T)	005.4	AA 04000	
	WEETS	JSSIE	030		TF		FB	1.0	099.5(085.5T)	010.0	AA 03000	
		JSSIE	010	FACF	IF		FB				AA 03000	
		KMBER	020	FAF	TF		FB	0.5	166.8(152.8T)	006.1	AA 02300	
		RW17	030	MAP	TF		FO	0.3	166.8(152.8T)	005.1	AT 00686	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		166.8(152.8T)		AA 01098	
	JSSIE	050		DF	R	FO				AA 03000	
	JSSIE	060		HM	R	FO		166.8(152.8T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	AROME	N415153.96	W0740439.65	N4151.899	W07404.661
	GELAW	N415645.41	W0734041.67	N4156.757	W07340.695
	JSSIE	N415239.93	W0735117.93	N4152.666	W07351.299
	KMBER	N414714.17	W0734733.93	N4147.236	W07347.566
	STUBY	N415407.54	W0732614.04	N4154.126	W07326.234
	WEETS	N415126.98	W0741151.51	N4151.450	W07411.859
	RW17	N414243.56	W0734428.40	N4142.726	W07344.473

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW17	00646	40

QUALITY
2
CHECKED

CITY AND STATE MILLBROOK, NY	ELEVATION: 698	THRE: 646	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:	SKY ACRES	RNAV	RNAV (GPS) RWY 17, AMDT 2	AMDT: 1A
				20 SEPTEMBER 2012	DATED: 11/18/2010