

U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in foot above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH											
FROM	T O	COURSE AND DISTANCE	ALTITUDE												
BEEPS WP	EBALE WP (TF) (FB)	056.26 / 14.09	3600	LNAV; RW10											
LYSAN WP	FALGI WP (TF) (FB)	265.23 / 11.92	3600												
EBALE WP (IAF)	HOBKA WP (TF) (FB)	008.79 / 5.00	2700	CLIMB TO 3000 DIRECT DETVE WP AND HOLD.											
FALGI WP (IAF)	HOBKA WP (TF) (FB)	188.77 / 5.00	2700												
HOBKA WP	CALUG WP (TF) (FB)	098.78 / 5.00	2000	ADDITIONAL FLIGHT DATA:											
RW10 (MAP)	DETVE WP (DF) (FO)		3000												
1. PT <u>NA</u> SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)				CALUG WP TO RW10: 3.04 / 40 FINAL SEGMENT: (TF) MAG VAR: 12W EPOCH YEAR: 90											
2. PROFILE STARTS AT HOBKA WP															
3. FAC: <u>098.86</u> FAF: <u>CALUG WP</u> DIST FAF TO MAP: <u>-</u> THLD: <u>4.83</u>															
4. MIN. ALT: <u>HOBKA WP 2700, CALUG WP 2000</u>															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: <u>34:1 IS NOT CLEAR</u>															
8. MSA FROM: <u>RW10 3700</u>															
MINIMUMS															
TAKEOFF:	<input checked="" type="checkbox"/>	STANDARD	SEE FAA FORM 8260-15 FOR THIS AIRPORT	ALTERNATE:	N	<input checked="" type="checkbox"/>									
CATEGORY	A		B		C		D	E							
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	1020	1	620	1020	1	620		NA			NA				
CIRCLING	1020	1	620	1060	1	660		NA			NA				
NOTES:															
USE SYRACUSE ALTIMETER SETTING															
GPS OR RNP-0.3 REQUIRED. DME/DME RNP-0.3 NA.															
CITY AND STATE		ELEVATION:		400 TDZE:		400		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP:	
WEEDSPORT, NY		Weedsp		ort		/ WHITFORDS		RNAV		OCT 3 2002 RNAV (GPS) RWY 10, ORIG				AMDT: NONE	
														DATE	