

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
BCE VORTAC	BEYAB (FO)	041.51 / 28.59	13100	LPV: DA LNAV/VNAV: DA LNAV: RW21
AXGEX (IAF)	BEYAB (NOPT) (FB)	284.11 / 38.76	12800	
OMUCE (IAF)	BEYAB (NOPT) (FB)	158.17 / 26.34	12800	CLIMB TO 12300 DIRECT OPAWO AND ON TRACK 235.29 TO CEXAT AND HOLD.
UJACI (IAF)	BEYAB (NOPT) (FB)	237.27 / 10.69	12800	
BEYAB (IF/IAF)	HIKMU (FB)	212.94 / 6.60	12000	
HIKMU	ZUGOV (FB)	212.88 / 2.00	11600	ADDITIONAL FLIGHT DATA: HOLD NE, RT, 226.36 INBOUND. CHART FAS OBST: 7609 TREE 374303N/1120852W 7849 AAO 374526N/1120610W 8294 AAO 374913N/1115848W DISTANCE TO THLD FROM 325 HATH: 0.89 NM. CHART VDP AT 1.40 MILES TO RW21* *LNAV ONLY. WAAS CHANNEL # 99516 REFERENCE PATH ID: W21A LTP HAE: 2282.4 M
ZUGOV	CUNYA (FB)	212.86 / 3.10	10700	
(SEE FORM 8260-10)				

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD NE BEYAB, RT, 212.94 INBOUND, 12800 FT. IN LIEU OF PT (IAF)
- FAC: 212.83 FAF: CUNYA DIST FAF TO MAP: 9.75 THLD: 9.75
- MIN. ALT: BEYAB 12800, HIKMU 12000, ZUGOV 11600, CUNYA 10700, WOBNO/3.10 NM TO RW21 8580*
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 10700 GS ALT AT: CUNYA 10700 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR
- MSA FROM: RW21 12400

MAG VAR: 14E EPOCH YEAR: 1980

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD					
CATEGORY ==>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	7879	1 1/8	325	7879	1 1/8	325	7879	1 1/8	325						
LNAV/VNAV DA	8006	1 1/2	452	8006	1 1/2	452	8006	1 1/2	452						
LNAV MDA	8040	1	486	8040	1	486	8040	1 3/8	486						
CIRCLING	8200	1	610	8220	1	630	8240	1 3/4	650						

NOTES:
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -30C (-22F) OR ABOVE 43C (109F).
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, PROCEDURE NA.
CHART NOTE: DME/DME RNP-0.3 NA.
(SEE FORM 8260-10)



CITY AND STATE BRYCE CANYON, UT	ELEVATION: 7590 THRE: 7554 AIRPORT NAME: BRYCE CANYON	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, AMDT 1 / 1 " 201	SUP: AMDT: ORIG DATED 03/10/2011
------------------------------------	---	------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
CUNYA (FAF)	WOBNO/3.10 NM TO RW21 (FB)	212.83 / 6.65	
WOBNO/3.10 NM TO RW21	RW21 (MAP) (FO)	212.77 / 3.10	
RW21 (MAP)	7879 MSL	212.77	
7879 MSL	OPAWO (FB)		
OPAWO	CEXAT (FO)	235.29 / 23.83	12300

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT OMUCE ON V244 WESTBOUND.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT AXGEX ON V208 SOUTHBOUND.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON BCE VORTAC AIRWAY RADIALS 323 CW 105.
 *LNAV ONLY

QUALITY
 1
 CHECKED

CITY AND STATE BRYCE CANYON, UT	ELEVATION: 7590	THRE: 7554	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, AMDT 1 / 1 " 201	SUP:
	AIRPORT NAME: BRYCE CANYON				AMDT: ORIG
					DATED: 03/10/2011

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBCE
RUNWAY	RW21
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W21A
LTP/FTP LATITUDE	374248.2510N
LTP/FTP LONGITUDE	1120811.3895W
LTP/FTP ELLIPSOIDAL HEIGHT	+22824
FPAP LATITUDE	374147.1100N
FPAP LONGITUDE	1120933.1400W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0496
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 C46B20F6

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+23023
FPAP ORTHOMETRIC HEIGHT	+23023



CITY AND STATE BRYCE CANYON, UT	ELEVATION: 7590 THRE: 7554	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 21, AMDT 1 / 1 " 201	SUP:
	AIRPORT NAME: BRYCE CANYON			AMDT: ORIG
				DATED: 03/10/2011

