Federal Aviation Administration

Transmittal Letter 16-11

April 8, 2016

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
26-May-16	SC	Aiken	Aiken Muni	6/4693	04/01/16	RNAV (GPS) RWY 25, Amdt 1B

AIRAC Date: 26 MAY 2016

FDC 6/4693 AIK IAP AIKEN MUNI, AIKEN, SC. RNAV (GPS) RWY 25, AMDT 1B... LNAV/VNAV VIS 1 ALL CATS. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. 34:1 IS CLEAR. CHANGE WHEN LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED. USE AUGUSTA RGNL AT BUSH FIELD ALTIMETER SETTING: INCREASE LPV ALL CATS DA TO 869 FT, LNAV/VNAV ALL CATS DA TO 927 FT AND ALL VISIBILITIES 3/8 MILE; INCREASE ALL MDA 120 FT AND CAT C/D VISIBILITES 1/4 MILE. CHANGE FOR INOPERATIVE ODALS NOTE TO READ: FOR INOPERATIVE ODALS, INCREASE LPV ALL CATS VISIBILITY TO 7/8 MILE. LNAV/VNAV ALL CATS TO 1 1/8 MILE AND LNAV CAT C/D TO 1 1/4 MILE. CHANGE FOR INOPERATIVE ODALS WHEN LOCAL ALTIMETER SETTING NOT RECEIVED. USE AUGUSTA RGNL AT BUSH FIELD ALTIMETER SETTING NOTE TO READ: FOR INOPERATIVE ODALS WHEN USING AUGUSTA RGNL AT BUSH FIELD ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 1/4 MILE, LNAV/VNAV ALL CATS TO 1 1/2 MILE AND LNAV CAT D TO 1 5/8 MILE. THIS IS RNAV (GPS) RWY 25, AMDT 1C. 1602161838-PERM