`U.S. Department of Transportation

Federal Aviation Administration

Transmittal Letter 18-16

June 15, 2018

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBE	FDC DATE	SUBJECT
19-Jul-18	WI	East Troy	East Troy Muni	8/3009	5/29/18	RNAV (GPS) RWY 8, Orig-B

AIRAC Date: 19 JULY 2018

FDC 8/3009 57C IAP EAST TROY MUNI, East Troy, WI. RNAV (GPS) RWY 8, ORIG-B... CHART VDP AT 1.11 NM TO RW08. CHART NOTE: RWY 8 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: VDP NA WHEN USING GENERAL MITCHELL INTL ALTIMETER SETTING. DELETE NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: CIRCLING NA TO RWYS 18 AND 36. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. ALTERNATE MINIMUMS: STANDARD. THIS IS RNAV (GPS) RWY 8, ORIG-C. 1805241151-PERM