

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F).

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WHITEMAN AFB ALTIMETER SETTING AND INCREASE ALL DA 61 FT AND ALL MDA 80 FT. INCREASE LNAV/VNAV ALL CATS AND LNAV CAT C VISIBILITY 1/4 MILE.

CHART NOTE: BARO-VNAV NA WITH WHITEMAN AFB ALTIMETER SETTING.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	134/30 CW 314/30 (NOPT)	134/22 CW 314/22	3900
2.	134/22 CW 314/22	ICEBA (IF/IAF) (FB)	3000
3.	314/30 CW 134/30	ICEBA (IF/IAF) (FO)	3000

CITY AND STATE
CLINTON, MO

ELEVATION: 823 THRE: 823
AIRPORT NAME:
CLINTON RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 22, AMDT 1
3 APRIL 2014

SUP:
AMDT: ORIG
DATED: 06/27/2013

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KGLY
RUNWAY	RW22
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W22A
LTP/FTP LATITUDE	382137.6520N
LTP/FTP LONGITUDE	0934045.2975W
LTP/FTP ELLIPSOIDAL HEIGHT	+02184
FPAP LATITUDE	382034.5200N
FPAP LONGITUDE	0934205.3100W
THRESHOLD CROSSING HEIGHT (TCH)	00051.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.50
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1528
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
<u>CRC REMAINDER</u>	43F2CC8A

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+02507
FPAP ORTHOMETRIC HEIGHT	+02507

CITY AND STATE

CLINTON, MO

ELEVATION: 823

THRE: 823

AIRPORT NAME:

CLINTON RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 22, AMDT 1

3 APRIL 2014

SUP:

AMDT: ORIG

DATED: 06/27/2013

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	ICEBA	ICEBA	010	IAF	HF	R	FO		224.1(225.1T)	004.0	AA 03000	
		ICEBA	010	FACF	IF		FB				AA 03000	
		YESUB	020	FAF	TF		FB	0.5	224.1(225.1T)	006.7	AA 02500	
		KOBGE	021	SDF	TF		FB	0.3	224.0(225.0T)	003.1	AA 01340	GS 01357
		RW22	030	MAP	TF		FO	0.3	224.0(225.0T)	001.3	AT 00874	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		224.0(225.0T)		AA 01115	
	SOGOY	050		DF		FO				AA 03000	
	SOGOY	060		HM	R	FO		043.8(044.8T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ICEBA	N382926.42	W0933049.39	N3829.440	W09330.823
	KOBGE	N382232.90	W0933935.22	N3822.548	W09339.587
	SOGOY	N381325.83	W0935107.01	N3813.431	W09351.117
	YESUB	N382443.61	W0933649.28	N3824.727	W09336.821
	RW22	N382137.65	W0934045.30	N3821.628	W09340.755

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW22	00823	51

CITY AND STATE CLINTON, MO	ELEVATION: 823	THRE: 823	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:	CLINTON RGNL	RNAV	RNAV (GPS) RWY 22, AMDT 1	AMDT: ORIG
				3 APRIL 2014	DATED: 06/27/2013