

**Federal Aviation
Administration**

Transmittal Letter 19-18

July 12, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/15/2019	MO	Clinton	Clinton Rgnl	9/4783	7/2/2019	RNAV (GPS) RWY 22, Amdt 1A

AIRAC Date: 15 AUGUST 2019

FDC 9/4783 GLY IAP CLINTON RGNL, Clinton, MO. RNAV (GPS) RWY 22, AMDT 1A... CIRCLING CAT B MDA 1300/HAA 477. DELETE NOTE: CIRCLING TO RWY 4 NA AT NIGHT. DELETE NOTE: DME/DME RNP -0.3 NA. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. DELETE NOTE: BARO-VNAV NA WITH WHITEMAN AFB ALTIMETER SETTING. CHART NOTE: CIRCLING RWY 4 NA AT NIGHT. CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: BARO-VNAV NA WHEN USING WHITEMAN ALTIMETER SETTING. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (113F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 22, AMDT 1B. 1907021231-PERM