

**Federal Aviation
Administration**

Transmittal Letter 19-23

September 20, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/7/2019	CA	Tracy	Tracy Muni	9/2665	9/3/2019	RNAV (GPS) RWY 12, Amdt 2A

AIRAC Date: 7 NOVEMBER 2019

FDC 9/2665 TCY IAP TRACY MUNI, Tracy, CA. RNAV (GPS) RWY 12, AMDT 2A...
PBN REQUIREMENTS NOTE: RNP APCH. 20:1 IS CLEAR. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STOCKTON ALTIMETER SETTING: INCREASE ALL DAS TO 507 FEET; INCREASE ALL MDAS 60 FEET AND VISIBILITY LNAV CAT C 1/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE STOCKTON ALTIMETER SETTING: INCREASE ALL DA TO 507 AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDA 60 FEET AND LNAV CAT C VISIBILITY 1/8 SM. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15 C OR ABOVE 54 C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15 C (5 F) OR ABOVE 54 C (130 F). ALTERNATE MINIMUMS: STANDARD. DELETE NOTE: DME/DME RNP-0.3 NA. THIS IS RNAV (GPS) RWY 12, AMDT 2B. 1908161829-PERM