

**Federal Aviation
Administration**

Transmittal Letter 19-23

September 20, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/7/2019	CA	Tracy	Tracy Muni	9/2673	9/3/2019	RNAV (GPS) RWY 26, Amdt 1B

AIRAC Date: 7 NOVEMBER 2019

FDC 9/2673 TCY IAP TRACY MUNI, Tracy, CA. RNAV (GPS) RWY 26, AMDT 1B...
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE
STOCKTON ALTIMETER SETTING: INCREASE LPV DA TO 496 FEET, INCREASE
LNAV/VNAV DA TO 553 FEET; INCREASE ALL MDAS 60 FEET AND VISIBILITY
LNAV CAT C 1/8 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT
RECEIVED, USE STOCKTON ALTIMETER SETTING: INCREASE LPV DA TO 496,
LNAV/VNAV DA TO 553; INCREASE ALL MDA 60 FEET AND LPV ALL CATS
VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS VISIBILITY 1/8 SM, AND LNAV CAT C
VISIBILITY 1/8 SM. ALTERNATE MINIMUMS: STANDARD. THIS IS RNAV (GPS)
RWY 26, AMDT 1C. 1908161833-PERM