

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW04 CLIMB TO 3000 DIRECT COPIV AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 224.79 INBOUND. CHART FAS OBST: 970 TREE 443616N/0884543W CHART: 987 TREE 443514N/0884656W DISTANCE TO THLD FROM 250 HAT: 0.62 NM. CHART VDP AT 1.07 NM TO RW04* *LNAV ONLY. WAAS CHANNEL # 86516 REFERENCE PATH ID: W04A CHART CIRCLING ICON. LTP HAE: 215.4 M						
BIPID		HIDEV (TF) (FO) (RNP 2.00)		207.86 / 5.10				3000								
IPUCO (IAF)		HIDEV (NOPT) (TF) (FB) (RNP 1.00)		134.42 / 6.65				3000								
EYITI (IAF)		HIDEV (NOPT) (TF) (FB) (RNP 1.00)		320.25 / 10.62				3000								
HIDEV (IF/IAF)		ARNDT (TF) (FB) (RNP 1.00)		044.54 / 5.93				2500								
ARNDT (FAF)		VUPLE/2.50 NM TO RW04 (TF) (FB) (RNP 0.30)		044.62 / 2.59												
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SW HIDEV, RT, 044.55 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 044.62 FAF: ARNDT DIST FAF TO MAP: 5.09 THLD: 5.09 4. MIN. ALT: HIDEV 3000, ARNDT 2500, VUPLE/2.50 NM TO RW04 1660* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2500 GS ALT AT: ARNDT 2500 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 52.0 34:1 IS NOT CLEAR 8. MSA FROM: RW04 2900										MAG VAR: 2W		EPOCH YEAR: 1995				
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD						
CATEGORY >>>>>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	1076	1	250	1076	1	250		NA			NA					
LNAV/VNAV DA	1229	1 3/8	403	1229	1 3/8	403		NA			NA					
LNAV MDA	1220	1	394	1220	1	394		NA			NA					
CIRCLING	1340	1	514	1340	1	514		NA			NA					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: RWY 9, 14, 27 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: RWY 4 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. (CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 826 TDZE: 826				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:				
CLINTONVILLE, WI		AIRPORT NAME:				CLINTONVILLE MUNI		RNAV (GPS) RWY 4, AMDT 2, 06/22/2017				AMDT: 1				
												DATED 02/11/2010				

QUALITY
 4
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
VUPLE/2.50 NM TO RW04	RW04 (MAP) (TF) (FO) (RNP 0.30)	044.62 / 2.50	
RW04 (MAP)	1076 MSL (CA)	044.62	
1076 MSL	COPUV (DF) (FO) (RNP 1.00)		3000

NOTES, (CONT.):

CHART NOTE: CIRCLING RWY 14 NA AT NIGHT.

CITY AND STATE
CLINTONVILLE, WI

ELEVATION: 826 TDZE: 826
AIRPORT NAME:
CLINTONVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 4, AMDT 2, 06/22/2017

SUP: 
AMDT: 1
DATED: 02/11/2010

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCLI
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	443635.6670N
LTP/FTP LONGITUDE	0884407.2440W
LTP/FTP ELLIPSOIDAL HEIGHT	+02154
FPAP LATITUDE	443741.1600N
FPAP LONGITUDE	0884242.6690W
THRESHOLD CROSSING HEIGHT (TCH)	00052.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1592
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
<u>CRC REMAINDER</u>	3A9C92B3

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02517
FPAP ORTHOMETRIC HEIGHT	+02517

CITY AND STATE
CLINTONVILLE, WI

ELEVATION: 826 TDZE: 826
AIRPORT NAME:
CLINTONVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 4, AMDT 2, 06/22/2017

SUP: 
AMDT: 1
DATED: 02/11/2010