

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION																
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW14 CLIMB TO 3000 DIRECT GIGKE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 319.09 INBOUND. CHART FAS OBST: 1009 TREE 443856N/0884547W CHART: 1294 TOWER 444027N/0884854W DISTANCE TO THLD FROM 279 HAT: 0.64 NM. WAAS CHANNEL # 42816 REFERENCE PATH ID: W14A CHART CIRCLING ICON. LTP HAE: 213.1 M						
RROBB		HURER (TF) (FB) (RNP 2.00)			069.44 / 24.43			3000								
BIPID		HURER (TF) (FB) (RNP 2.00)			326.70 / 10.82			3000								
HURER (IAF)		ICOSI (NOPT) (TF) (FB) (RNP 1.00)			048.78 / 5.00			3000								
JEVBI (IAF)		ICOSI (NOPT) (TF) (FB) (RNP 1.00)			229.01 / 16.31			3000								
ICOSI (IF/IAF)		COKVO (TF) (FB) (RNP 1.00)			138.84 / 6.08			2700								
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD NW ICOSI, RT, 138.83 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																
3. FAC: 138.88 FAF: COKVO DIST FAF TO MAP: 5.20 THLD: 5.20																
4. MIN. ALT: ICOSI 3000, COKVO 2700, FIMAV/2.30 NM TO RW14 1680*																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: 2700 GS ALT AT: COKVO 2700 OM: _____ MM: _____ IM: _____																
7. GS ANGLE: 3.30 TCH: 60.0 34:1 IS NOT CLEAR																
8. MSA FROM: RW14 2900																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD				
CATEGORY ==>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	1101	1	279	1101	1	279		NA			NA					
LNAV/VNAV DA	1329	1 1/2	507	1329	1 1/2	507		NA			NA					
LNAV MDA	1260	1	438	1260	1	438		NA			NA					
CIRCLING	1340	1	514	1340	1	514		NA			NA					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: RWY 9, 14, 27 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BIPID ON V191 SOUTHEAST BOUND. (CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 826 TDZE: 822				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:				
CLINTONVILLE, WI		AIRPORT NAME:				CLINTONVILLE MUNI		RNAV (GPS) RWY 14, AMDT 2, 06/22/2017				AMDT: 4				
												DATED 02/11/2010				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
COKVO (FAF)	FIMAV/2.30 NM TO RW14 (TF) (FB) (RNP 0.30)	138.88 / 2.90	
FIMAV/2.30 NM TO RW14	RW14 (MAP) (TF) (FO) (RNP 0.30)	138.88 / 2.30	
RW14 (MAP)	1101 MSL (CA)	138.88	
1101 MSL	GIGKE (DF) (FO) (RNP 1.00)		3000

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT JEVBI ON V217 NORTHWEST BOUND.

*LNAV ONLY

CHART NOTE: STRAIGHT-IN AND CIRCLING RWY 14 NA AT NIGHT.

CITY AND STATE
CLINTONVILLE, WI

ELEVATION: 826 TDZE: 822
AIRPORT NAME:
CLINTONVILLE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 14, AMDT 2, 06/22/2017

SUP: **QUALITY 4**
AMDT: **1 CHECKED**
DATED: 02/11/2010

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCLI
RUNWAY	RW14
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W14A
LTP/FTP LATITUDE	443704.9690N
LTP/FTP LONGITUDE	0884417.6675W
LTP/FTP ELLIPSOIDAL HEIGHT	+02131
FPAP LATITUDE	443559.8630N
FPAP LONGITUDE	0884252.5240W
THRESHOLD CROSSING HEIGHT (TCH)	00060.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.30
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1352
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

FAE4D494

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02495
FPAP ORTHOMETRIC HEIGHT	+02495

CITY AND STATE

CLINTONVILLE, WI

ELEVATION: 826

TDZE: 822

AIRPORT NAME:

CLINTONVILLE MUNI

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 14, AMDT 2, 06/22/2017

SUP:

AMDT:

DATED:

 QUALITY
4
1
CHECKED
02/11/2010