

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
TACAN STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.23

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KGV T	<u>PROCEDURE NAME</u> TACAN RWY 17	<u>ORIGINAL/AMENDMENT</u> ORIG-C	<u>CITY</u> GREENVILLE	<u>STATE</u> TX		
<u>AIRPORT ELEVATION</u> 535	<u>TDZE</u> 534	<u>SUPERSEDED</u> TACAN RWY 17	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>DATED</u> 04/21/2022	<u>MAG VAR</u> 5E	<u>EPOCH YEAR</u> 1995
<u>FACILITY</u> MJF TACAN	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 29 DECEMBER 2022	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
BYP VORTAC		WOLFI/MJF 15.00 DME	NOPT				147.73	14.90	3000
WOLFI/MJF 15.00 DME	IF/IAF	WOMDI/MJF 6.00 DME					167.00	9.00 (MJF R-347)	2200

MISSED APPROACH

MAP:

TIDYL/MJF 1.80 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1200 THEN CLIMBING RIGHT TURN TO 3000 ON MJF TACAN R-186 TO CAJAN/MJF 15.00 DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD N WOLFI, RT, 167.00 INBOUND, 3000 FT. IN LIEU OF PT (IAF), MAX 8000.
3. FAC: 167.00 FAF: WOMDI/MJF 6.00 DME DIST FAF TO MAP: DIST FAF TO THLD: 5.23
4. MIN ALT: WOLFI/MJF 15.00 DME 3000, WOMDI/MJF 6.00 DME 2200
8. MSA FROM: MJF TACAN 2400, ESA W/IN 100 NM 4000

EQUIPMENT REQUIREMENTS NOTES:

NOTES:

CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-17 CAT E VISIBILITY TO 1 1/2 SM.

QUALITY
22
CHECKED

