

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE**

TITLE 14 CFR PART 97.33

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> ANAKTUVUK PASS	<u>AIRPORT ID</u> PAKP	<u>PROCEDURE NAME</u> RNAV (GPS)-A	<u>ORIGINAL/AMENDMENT</u> 2	<u>CITY</u> ANAKTUVUK PASS	<u>STATE</u> AK	
<u>AIRPORT ELEVATION</u> 2106	<u>TDZE</u>	<u>SUPERSEDED</u> RNAV (GPS)-A	<u>ORIGINAL/AMENDMENT</u> 1A	<u>DATED</u> 10/17/2013	<u>MAG VAR</u> 16E	<u>EPOCH YEAR</u> 2020
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 21 MAY 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TAA

FROM	FIX TYPE	TO	FIX TYPE	ALTITUDE
1. 308/30 CW 073/30	NOPT	AKUMY	IF/IAF	9000
2. 073/30 CW 128/30	NOPT	073/25 CW 128/25		10000
3. 073/25 CW 128/25		AKUMY	IF/IAF	9000
4. 128/30 CW 218/30		HUXOD	IAF	10000
5. 218/30 CW 308/30		LICIT	IAF	9000

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
LICIT	IAF	AKUMY	NOPT	TF	FB	1.00	308.47	10.00	9000
HUXOD	IAF	AKUMY	NOPT	TF	FB	1.00	127.99	10.00	9000
AKUMY	IF/IAF	GESTE		TF	FB	1.00	038.23	13.03	7400
GESTE	FAF	UPINE	MAP	TF	FO	0.30	038.67	9.00	
UPINE	MAP	2506 MSL		CA			038.67		
2506 MSL		DESCA		DF	FB	1.00			
DESCA		HEPKU		TF	FB	1.00	001.95	21.30	
HEPKU		ZETUV		TF	FO	1.00	070.32	26.61	10000

QUALITY
21
CHECKED

MISSED APPROACH

MAP:

UPINE

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 10000 DIRECT DESCA AND ON TRACK 001.95 TO HEPKU AND TRACK 070.32 TO ZETUV AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT

SIDE OF COURSE

OUTBOUND

FT WITHIN

MILES OF (IAF)

2. HOLD SW AKUMY, RT, 038.23 INBOUND, 9000 FT. IN LIEU OF PT (IAF), MAX 12000.

3. FAC: 038.67

FAF: GESTE

DIST FAF TO MAP: 9.00

DIST FAF TO THLD:

4. MIN ALT: AKUMY 9000, GESTE 7400

5. DIST TO THLD FROM OM:

MM:

IM:

150 HAT:

GS ANT:

6. MIN GP INCPT:

GP ALT AT FAF :

OM:

MM:

IM:

7. GP ANGLE:

34:1:

20:1:

TCH:

8. MSA FROM:

PBN REQUIREMENTS NOTE:

RNP APCH.

NOTES:

CHART NOTE: CIRCLING NA W OF RWY 2-20.

ADDITIONAL FLIGHT DATA:

FAC CROSSES RWY 2 THLD.
CHART CIRCLING ICON.
FAS OBST: 3399 AAO 680527N/1515754W.
HOLD E, RT, 271.60 INBOUND

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ CAT A, B 3600-2, CAT C, D 4200-3

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
CIRCLING	5620	1 1/4	3514	5620	1 1/2	3514	6240	3	4134	6240	3	4134			



