

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW36							
ZABDU (IF/IAF)		OLOCI (TF) (FB) (RNP 1.00)		004.44 / 6.25				2300		CLIMB TO 2300 DIRECT JUMAK AND HOLD.							
OLOCI (FAF)		RW36 (MAP) (TF) (FO) (RNP 0.30)		004.44 / 4.92													
RW36 (MAP)		1073 MSL (CA)		004.44													
1073 MSL		JUMAK (DF) (FO) (RNP 1.00)						2300		ADDITIONAL FLIGHT DATA: HOLD N, RT, 184.43 INBOUND. CHART FAS OBST: 948 STACK 412232N/0833839W. OLOCI TO RW36: 3.04/40							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																	
2. HOLD S ZABDU, RT, 004.44 INBOUND, 2400 FT. IN LIEU OF PT (IAF)																	
3. FAC: 004.44 FAF: OLOCI DIST FAF TO MAP: 4.92 THLD: 4.92																	
4. MIN. ALT: ZABDU 2400, OLOCI 2300																	
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																	
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																	
7. GS ANGLE: _____ TCH: 20:1 IS NOT CLEAR 34:1 IS NOT CLEAR																	
8. MSA FROM: RW36 3100																	
MAG VAR: 5W EPOCH YEAR: 1985																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X							
CATEGORY =====>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LNAV MDA	1260	1	588	1260	1	588		NA			NA						
CIRCLING	1300	1	627	1300	1	627		NA			NA						
NOTES: CHART NOTE: RWY 36 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. PBN REQUIREMENTS NOTE: RNP APCH. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TOLEDO EXPRESS ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET. CHART NOTE: STRAIGHT-IN AND CIRCLING RWY 36 NA AT NIGHT.																	
CITY AND STATE BOWLING GREEN, OH		ELEVATION: 673 TDZE: 672 AIRPORT NAME: WOOD COUNTY				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG-C 24 MAY 2018				SUP: AMDT: ORIG-B DATED 05/26/2016					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE
BOWLING GREEN, OH

ELEVATION: 673 TDZE: 672
AIRPORT NAME:
WOOD COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 36, ORIG-C
24 MAY 2018

SUP:
AMDT: ORIG-B
DATED: 05/26/2016

QUALITY
10
CHECKED