

**Federal Aviation
Administration**

Transmittal Letter 21-21

August 20, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/7/2021	MN	Minneapolis	Flying Cloud	1/4897	7/8/2021	RNAV (GPS) RWY 10R, Orig-B

AIRAC Date: 7 OCTOBER 2021

FDC 1/4897 FCM IAP FLYING CLOUD, MINNEAPOLIS, MN. RNAV (GPS) RWY 10R, ORIG-B...
DELETE NOTE: NIGHT LANDING: RWY 18/36 NA. CHART NOTE: WHEN CIRCLING TO RWY 18, 36 AT NIGHT, OPERATIONAL VGSI REQUIRED, REMAIN ON OR ABOVE VGSI GLIDEPATH UNTIL THRESHOLD. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. PROFILE VIEW: CHART MAX HOLDING ALTITUDE AT ZAMUD 6000. DELETE TDZE 905. CHART TDZE 906. LPV DA/HAT ALL CATS 1106/200. LNAV/VNAV DA/HAT ALL CATS 1237/331. LNAV MDA/HAT ALL CATS 1280/374. THIS IS RNAV (GPS) RWY 10R, ORIG-C. 2107062110-PERM