

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KPGR	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 4	<u>ORIGINAL/AMENDMENT</u> ORIG-C	<u>CITY</u> PARAGOULD	<u>STATE</u> AR		
<u>AIRPORT ELEVATION</u> 290	<u>TDZE</u> 290	<u>SUPERSEDED</u> RNAV (GPS) RWY 4	<u>ORIGINAL/AMENDMENT</u> ORIG-B	<u>DATED</u> 01/02/2020	<u>MAG VAR</u> 1E	<u>EPOCH YEAR</u> 1995
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 7 OCTOBER 2021	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
ARG VORTAC		BALYA		TF	FB	1.00	124.44	12.24	3000
COXAX	IAF	AYATO	NOPT	TF	FB	1.00	315.35	5.00	2500
BALYA	IAF	AYATO	NOPT	TF	FB	1.00	135.27	5.00	2500
AYATO	IF/IAF	PAWGE		TF	FB	1.00	045.31	6.01	2000
PAWGE	FAF	TACOS/2.00 NM TO RW4		TF	FB	0.30	045.37	3.15	
TACOS/2.00 NM TO RW4		RW4	MAP	TF	FO	0.30	045.37	2.00	
RW4	MAP	690 MSL		CA			045.37		
690 MSL		CUBIN		DF	FO	1.00			3000

MISSED APPROACH

MAP:

LNAV: RW4

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 3000 DIRECT CUBIN AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:



PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. HOLD SW AYATO, RT, 045.31 INBOUND, 2500 FT. IN LIEU OF PT (IAF), MAX 14000.

3. FAC: 045.37 FAF: PAWGE DIST FAF TO MAP: 5.15 DIST FAF TO THLD: 5.15

4. MIN ALT: AYATO 2500, PAWGE 2000, TACOS/2.00 NM TO RW4 980

5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: MM: IM:

6. MIN GP INCPT: GP ALT AT FAF : OM: MM: IM:

7. GP ANGLE: 34:1: IS NOT CLEAR 20:1: IS CLEAR TCH:

8. MSA FROM: RW04 3100

PBN REQUIREMENTS NOTE:

RNP APCH - GPS

NOTES:

CHART NOTE: CIRCLING NA TO RWYS 8 AND 26.
CHART NOTE: RWY 4 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON ARG VORTAC AIRWAY RADIALS 058 CW 211.
CHART NOTE: USE JONESBORO ALTIMETER SETTING; WHEN NOT RECEIVED, USE WALNUT RIDGE ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET.

ADDITIONAL FLIGHT DATA:

CHART JONESBORO MUNI ASOS
CHART CIRCLING ICON.
HOLD NE, RT, 225.52 INBOUND.
CHART FAS OBST: 440 TOWER (05-092148) 360339N/0903133W.
CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.

MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LNAV MDA	800	1 1/4	510	800	1 1/4	510		NA			NA				
CIRCLING	860	1 1/4	570	1000	1 1/4	710		NA			NA				



CHANGES - REASONS

1. DELETED MAW FEEDER AND ASSOCIATED PROCEDURE NA FOR ARRIVAL NOTE - MAW SCHEDULED DECOMMISSIONING.
2. DELETED GQE FEEDER AND ASSOCIATED PROCEDURE NA FOR ARRIVAL NOTE - GQE SCHEDULED DECOMMISSIONING.
3. INCORPORATED NOTAM 9/1430, RNAV (GPS) RWY 4, ORIG-B INTO THIS AMENDMENT - INCLUDED FOR CURRENT AMENDMENT.
4. CHANGED BACKUP ALTIMETER NOTE FROM: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JONESBORO ALTIMETER SETTING (9/1430) TO: USE JONESBORO ALTIMETER SETTING; WHEN NOT RECEIVED, USE WALNUT RIDGE ALTIMETER SETTING - AIRPORT HAS NO LOCAL ALTIMETER/FPT.
5. ADDED MAX HOLD-IN-LIEU ALTITUDE: 14000 TO PROFILE LINE 2 - REQUIRED BY CRITERIA.
6. UPDATED PBN REQUIREMENTS NOTE TO RNP APCH - GPS - REQUIRED BY CRITERIA.
7. ADDED CHART JONESBORO MUNI ASOS - CHART PRIMARY REMOTE ALTIMETER SOURCE.
8. NEW FAS OBSTACLE: 440 TOWER (05-092148) 360339.36N/0903132.88W - NEW OBSTACLE EVALUATION.
9. RAISED STEP ALTITUDE FROM 920 TO 980 - NEW CONTROLLING OBSTACLE.
10. UPDATED PROCEDURE NA NOTE FROM: PROCEDURE NA FOR ARRIVALS AN ARG VORTAC AIRWAY RADIALS 089 CW 149 TO: PROCEDURE NA FOR ARRIVALS AN ARG VORTAC AIRWAY RADIALS 058 CW 211 - UPDATED TO CURRENT CRITERIA.
11. CHANGED ALTERNATE MINIMUMS TO NA - REMOTE ALTIMETER IN USE.
12. ADDED CHART CIRCLING ICON TO ADDITIONAL FLIGHT DATA - NEW CIRCLING RADII APPLIED.
13. RAISED CIRCLING CAT B MDA/HAA FROM 860/570 TO 1000/710 - NEW CIRCLING RADII APPLIED/NEW OBSTACLE EVALUATION.

COORDINATED WITH:

A4A ☐ ALPA ☐ AOPA ☒ APA ☐ HAI ☐ NBAA ☒ OTHER: ZME, APT MGR, ST AV DIR

FLIGHT CHECKED BY

MICHAEL S MILLER

Digitally signed by

LONNIE EVERHART

Aug 16, 2021

OFFICE

FICO

DATE

08/11/2021

DEVELOPED BY

DAVID TEFFETELLER (THERON CYRUS)

Digitally signed by

LONNIE EVERHART

Aug 16, 2021

OFFICE

AJV-A433

DATE

04/30/2021

APPROVED BY

LONNIE EVERHART

Digitally signed by

LONNIE EVERHART

Aug 16, 2021

OFFICE

AJV-A430

DATE

TITLE
MANAGER

8/31/2021: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 8/16/2021.

1. ADDED SM IN HELICOPTER NOTE.

