

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
LIYGE (IAF)	JIXUB (NOPT) (FB)	347.26 / 5.00	3000	LNAV: RW26 CLIMB TO 3000 DIRECT NURYI AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 076.99 INBOUND. CHART FAS OBST: 1207 TOWER 342138N/0830525W IYITE TO RW26: 3.04/40. CHART TOCCOA AWOS-3, 119.625.
KIYED (IAF)	JIXUB (NOPT) (FB)	167.22 / 5.00	3000	
JIXUB (IF/IAF)	IYITE (FB)	257.24 / 6.10	2500	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD E JIXUB, RT, 257.24 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 257.17 FAF: IYITE DIST FAF TO MAP: 4.86 THLD: 4.86
- MIN. ALT: JIXUB 3000, IYITE 2500
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 5W

EPOCH YEAR: 2005

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	X									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1520	1	630	1520	1	630	1520	1 3/4	630	1520	2	630			
CIRCLING	1520	1	630	1520	1	630	1520	1 3/4	630	1580	2 1/4	690			

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: USE TOCCOA ALTIMETER SETTING; WHEN NOT RECEIVED, USE ANDERSON REGIONAL ALTIMETER
SETTING AND INCREASE ALL MDA 20 FEET.

CITY AND STATE CANON, GA	ELEVATION: 890 TDZE: 890 AIRPORT NAME: FRANKLIN COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 26, ORIG 25 SEP 2008	SUP: AMDT: NONE DATED
---------------------------------	--	------------------------------	--	-----------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	167/30 CW 347/30 (NOPT)	167/10 CW 347/10	4000
2.	167/10 CW 347/10	JIXUB (IF/IAF) (FB)	3000
3.	347/30 CW 077/30	347/20 CW 077/20	4000
4.	347/20 CW 077/20	LIYGE (IAF) (FB)	3000
5.	077/30 CW 167/30	077/10 CW 167/10	4600
6.	077/10 CW 167/10	KIYED (IAF) (FB)	3000

CITY AND STATE

CANON, GA

ELEVATION: 890 TDZE: 890

AIRPORT NAME:

FRANKLIN COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 26, ORIG

25 SEP 2008

SUP:

AMDT: NONE

DATED:

QUALITY
2
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE CANON, GA	ELEVATION: 890 TDZE: 890 AIRPORT NAME: FRANKLIN COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 26, ORIG 25 SEP 2008	SUP:
				AMDT: NONE
				DATED:

QUALITY
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	JIXUB	JIXUB	010		HF	R	FB		257.2(252T)	004.0	03000
	KIYED	KIYED	010	IAF	IF		FB				
	KIYED	JIXUB	020		TF		FB	1.0	167.2(162T)	005.0	03000
	LIYGE	LIYGE	010	IAF	IF		FB				
	LIYGE	JIXUB	020		TF		FB	1.0	347.3(342T)	005.0	03000
		JIXUB	010	FACF	IF		FB				03000
		IYITE	020	FAF	TF		FB	0.5	257.2(252T)	006.1	02500
		RW26	030	MAP	TF		FO	0.3	257.2(252T)	004.9	00930

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE
	NURYI	040		DF		FO	1.0			03000
	NURYI	050		HM	R	FO	2.0	077.0(072T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	IYITE	N342202.49	W0830146.99	N3422.042	W08301.783
	JIXUB	N342354.45	W0825446.24	N3423.908	W08254.771
	KIYED	N342840.63	W0825636.93	N3428.677	W08256.616
	LIYGE	N341908.24	W0825255.76	N3419.137	W08252.929
	NURYI	N341651.12	W0832107.59	N3416.852	W08321.127
	RW26	N342032.85	W0830722.55	N3420.548	W08307.376

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW26	00890	40

CITY AND STATE
CANON, GA

ELEVATION: 890 TDZE: 890
 AIRPORT NAME:
 FRANKLIN COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 26, ORIG
 25 SEP 2008

SUP:
 AMDT: NONE
 DATED:

QUALITY
CHECKED