U.S. Department of Transportation

800 Independence Ave., S.W. Washington, D.C. 20591

Federal Aviation Administration

**Transmittal Letter 16-08** 

February 26, 2016

## PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
31-Mar-16	MI	Pellston	Pellston Rgnl Airport Of Emmet County	6/2212	02/17/16	RNAV (GPS) RWY 23, Orig-A

## EFFECTIVE 31 MARCH 2016

FDC 6/2212 PLN IAP PELLSTON RGNL AIRPORT OF EMMET COUNTY, PELLSTON, MI. RNAV (GPS) RWY 23, ORIG-A... CIRCLING CAT B/C MDA 1300/HAA 579. CHANGE WHEN LOCAL ALTIMETER SETTING NOT RECEIVED NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HARBOR SPRINGS ALTIMETER SETTING AND INCREASE LPV DA TO 1085, LNAV/VNAV DA TO 1137 AND ALL VISIBILITIES 1/4 MILE, AND ALL MDA 40 FT; INCREASE CIRCLING CAT C VISIBILITY 1/4 MILE. THIS IS RNAV (GPS) RWY 23, ORIG-B. 1602091938-PERM