

**Federal Aviation  
Administration**

**Transmittal Letter 21-11**

**April 2, 2021**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: .....EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
5/20/2021	WY	Worland	Worland Muni	1/8477	3/23/2021	RNAV (GPS) RWY 16, Orig-B

**AIRAC Date: 20 MAY 2021**

FDC 1/8477 WRL IAP WORLAND MUNI, WORLAND, WY. RNAV (GPS) RWY 16, ORIG-B...  
CIRCLING CAT A/B/C MDA FROM 4920/668. CAT D MDA 5020/HAA 768. CIRCLING CAT D  
VIS 2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED,  
USE GREYBULL ALTIMETER SETTING: INCREASE LPV DA TO 4574 FEET, LNAV/VNAV DA  
TO 4616 FEET, AND ALL MDAS 140 FEET; INCREASE LPV, LNAV/VNAV AND LNAV ALL  
CATS, AND CIRCLING CAT C/D VISIBILITIES 1/2 SM. ALTERNATE MINIMUMS: STANDARD  
EXCEPT CAT D 800-2 1/2, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV  
(GPS) RWY 16, ORIG-C. 2103231416-PERM