

**Federal Aviation
Administration**

Transmittal Letter 26-16

June 5, 2026

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/9/2026	NY	Batavia	Genesee County	6/3380	5/27/2026	RNAV (GPS) RWY 28, Orig-A

AIRAC Date: 9 JULY 2026

FDC 6/3380 GVQ IAP GENESEE COUNTY, BATAVIA, NY. RNAV (GPS) RWY 28, ORIG-A...
LNAV CAT C VISIBILITY 5/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS
NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART
VDP AT 0.92 NM TO RW28. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED, USE ROC ALTIMETER SETTING: INCREASE LPV DA
TO 1263 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1466 FEET
AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CAT
C 3/8 SM AND CIRCLING VISIBILITY CAT C/D 1/2 SM. CHANGE BARO-VNAV AND VDP NA
TO READ: BARO-VNAV AND VDP NA WHEN USING ROC ALTIMETER SETTING. CHANGE
FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-
VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. DELETE NOTE FOR
INOPERATIVE MALSR, WHEN USING ROCHESTER ALTIMETER SETTING INCREASE LPV
VISIBILITY ALL CATS TO 1 1/4 MILE. CHART NOTE: INOPERATIVE TABLE DOES NOT
APPLY TO LNAV CAT D. CHANGE NOTE TO READ: FOR INOPERATIVE ALS, INCREASE
LNAV CAT C VISIBILITY TO 1 SM. THIS IS RNAV (GPS) RWY 28, ORIG-B. 2605271908-PERM