

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: TRV 12.55 DME FIX CLIMB TO 800 THEN CLIMBING RIGHT TURN TO 2600 ON HEADING 270 AND TRV VORTAC R-185 TO BIWIK/TRV 9.00 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 004.99 INBOUND. CHART FAS OBST: 154 TREE 273040N/0802109W GOLDY TO RW14: 3.40/46.							
TRV VORTAC (IF/IAF)		LADDY/TRV 7.00 DME		156.95 / 7.00				2000									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NW TRV VORTAC, RT, 156.95 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC <u>156.95</u> FAF <u>LADDY/TRV 7.00 DME</u> DIST FAF TO MAP <u> </u> THLD <u>5.55</u> 4. MIN. ALT <u>LADDY 2000, GOLDY/TRV 10.58 DME 780</u> 8. MSA FROM: <u>TRV VORTAC 1600</u>														MAG VAR: 7W		EPOCH YEAR: 2015	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-14	420	1	397	420	1	397	420	1 1/8	397	420	1 1/8	397					
CIRCLING	460	1	437	480	1	457	480	1 1/2	457	580	2	557					
NOTES: CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON TRV VORTAC AIRWAY RADIALS 231 CW 350. CHART PROFILE NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: STRAIGHT-IN/CIRCLING RWY 14 PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)																	
CITY AND STATE FORT PIERCE, FL		ELEVATION: 23 THRE: 23 AIRPORT NAME: ST LUCIE COUNTY INTL		FACILITY IDENTIFIER: TRV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 14, AMDT 9A, 09/20/2012						SUP					
												AMDT 9					
												DATE 02/09/2012					

4
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VERO BEACH ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET; INCREASE S-14 CATS C/D VISIBILITY 1/8 MILE.

QUALITY
A
CHECKED

CITY AND STATE

FORT PIERCE, FL

ELEVATION: 23

THRE: 23

AIRPORT NAME:

ST LUCIE COUNTY INTL

FACILITY
IDENTIFIER:
TRV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR/DME RWY 14, AMDT 9A, 09/20/2012

SUP:

AMDT: 9

DATED: 02/09/2012