U.S. Department of Transportation

Federal Aviation Administration

Transmittal Letter 19-24

December 10, 2021

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

......EFFECTIVEUPONPUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/7/2019	TN	SMITHVILLE	SMITHVILLE MUNI	9/5019	9/26/2019	RNAV (GPS) RWY 6 AMDT 3A

AIRAC Date: 27 JANUARY 2022

FDC 9/5019 0A3 IAP SMITHVILLE MUNI, Smithville, TN. RNAV (GPS) RWY 6, AMDT 3A... DELETE CIRCLING MINIMUMS. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. CHART NOTE: RWY 6 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: USE SPARTA ALTIMETER SETTING; WHEN NOT RECEIVED, USE TULLAHOMA ALTIMETER SETTING AND INCREASE ALL DA 56 FT AND ALL MDA 60 FT. INCREASE LPV ALL CATS, LNAV CAT C VISIBILITY 1/4 MILE; INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE. DELETE NOTE: USE SPARTA ALTIMETER SETTING; WHEN NOT RECEIVED, USE TULLAHOMA ALTIMETER SETTING AND INCREASE ALL DA 56 FT AND ALL MDA 60 FT. INCREASE LPV ALL CATS, LNAV CAT C AND CIRCLING CAT C VISIBILITY 1/4 MILE; INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 MILE. THIS IS RNAV (GPS) RWY 6, AMDT 3B. 1909251624-PERM