U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27									Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
				IINAL ROU	JTES							MISSED A	PPROACH	4		
FROM			TO COURSE				AND DISTANCE ALTITUD			MAP: TII	NDB					
										CLIMB T	O 2400 THEN	I RIGHT TUR	N DIRECT	TII NDB A	ND HOLD.	
												250.00 INBO 100 AAO 41		5933W.		
1. PT L SIDE OF C	OURSE 07	0.00 Ol	JTBOUND 2	2400 FT W	ITHIN 1	MILES O	F	TII ND	B	<u>(</u> IAF)						
2																
							MINIMUMS									
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNA		X							
CATEGORY ====>					В			С			D	T		E		
S-24	MDA	VIS	HAT/HAA	MDA	VIS 1	HAT/HAA	MDA 1460	VIS	HAT/HAA 675	MDA 1460	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
CIRCLING	1460 1460	<u>1</u> 1	675	1460 1460		675 674	1460	1 7/8 2	674	1460	2 2 1/4	675 674			_	
	1400		014	1400		014		-			2.04	014		1		
NOTES: CHART NOTE: RWY 24 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FINDLAY ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND INCREASE S-24 CAT C VISIBILITY 1/8 SM. CHART NOTE: STRAIGHT-IN RWY 24 NA AT NIGHT, CIRCLING RWY 24 NA AT NIGHT.																
CITY AND STATE			ELEVATION: 7		85	FACILITY		PROCEDURE		NO./AMDT NO./EFFECTIVE DATE:						
TIFFIN, OH			AIRPORT NAME:				IDENTIFIE	२:			NDB RWY 24, AMDT 7D			MDT	7C	
							19 JULY 2018					06/25/2015				
		<u> </u>	<u> </u>					1								