Federal Aviation Administration

Transmittal Letter 20-03

December 13, 2019

PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53 (AVAILABLE ON THE WEB AT HTTP://NFDC.FAA.GOV)

The enclosed Standard Instrument Approach Procedures, Departure Procedures/Takeoff Minimums and Fix Actions are effective as indicated.

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/30/2020	TX	Taylor	Taylor Muni	9/5949	11/20/2019	RNAV (GPS) RWY 17, Orig-A

AIRAC Date: 30 JANUARY 2020

FDC 9/5949 T74 IAP TAYLOR MUNI, Taylor, TX. RNAV (GPS) RWY 17, ORIG-A... DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: BARO-VNAV NA. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. DELETE NOTE: USE AUSTIN EXECUTIVE ALTIMETER SETTING; WHEN NOT RECEIVED USE GEORGETOWN ALTIMETER SETTING AND INCREASE ALL DA TO 909 AND ALL VISIBILITIES 1/8 MILE; INCREASE ALL MDA 40 FEET. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUSTIN-EXECUTIVE ALTIMETER SETTING AND INCREASE ALL DA TO 914 FEET AND ALL MDA 40 FEET. DELETE ALTERNATE MINIMUMS NA. ADD ALTERNATE MINIMUMS STANDARD, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART VDP AT 1.00 NM TO RW17*. *LNAV ONLY. CHART NOTE: VDP AND BARO-VNAV NA WHEN USING AUSTIN-EXECUTIVE ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 17, ORIG-B. 1909261520-PERM