

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION						INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES																MISSED APPROACH									
FROM				TO				COURSE AND DISTANCE				ALTITUDE		LP: RW02 LNAV: RW02 CLIMBING RIGHT TURN TO 6300 DIRECT NEDNE AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 2549 AAO 670947N/1501900W FAS OBST: 2699 AAO 670947N/1501842W WAAS CHANNEL # 93727 REFERENCE PATH ID: W02A CHART CIRCLING ICON. CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES. CHART BETTLES ASOS-3 LTP HAE: 322.8 M											
HULUD (IAF)				NEDNE (NOPT) (TF) (FB) (RNP 1.00)				286.13 / 8.50				6300													
IYIPE (IAF)				NEDNE (NOPT) (TF) (FB) (RNP 1.00)				105.57 / 8.50				6300													
NEDNE (IF/IAF)				KAKGE (TF) (FB) (RNP 1.00)				015.85 / 7.00				4400													
KAKGE (FAF)				RW02 (MAP) (TF) (FO) (RNP 0.30)				015.99 / 8.50																	
RW02 (MAP)				1446 MSL (CA)				015.99																	
1446 MSL				NEDNE (DF) (FO) (RNP 1.00)								6300													
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S NEDNE, RT, 015.85 INBOUND, 6300 FT. IN LIEU OF PT (IAF) 3. FAC: 015.99 FAF: KAKGE DIST FAF TO MAP: 8.50 THLD: 8.50 4. MIN. ALT: NEDNE 6300, KAKGE 4400 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: _____																MAG VAR: 16E				EPOCH YEAR: 2020					
MINIMUMS																									
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		X															
CATEGORY =====>		A			B			C			D			E											
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA										
LP MDA	4160	1 1/4	3116	4160	1 1/2	3116	4160	3	3116		NA														
LNAV MDA	4340	1 1/4	3296	4340	1 1/2	3296	4340	3	3296		NA														
CIRCLING	4340	1 1/4	3294	4340	1 1/2	3294	4340	3	3294		NA														
NOTES: CHART NOTE: CIRCLING NA FOR CATS B AND C WEST OF RWY 2-20. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: RWY 2 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: USE BETTLES ALTIMETER SETTING, WHEN NOT RECEIVED, PROCEDURE NA. CHART NOTE: CIRCLING RWY 20 NA AT NIGHT.																									
CITY AND STATE				ELEVATION: 1046 TDZE: 1044				FACILITY IDENTIFIER: RNAV				PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP: RNAV (GPS) RWY 1									
COLDFOOT, AK				AIRPORT NAME: COLDFOOT								RNAV (GPS) RWY 2, AMDT 2				AMDT: 1C									
												12 OCTOBER 2017				DATED 12/10/2015									



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	286/30 CW 106/30 (NOPT)	286/4 CW 106/4	7000
2.	286/4 CW 106/4	NEDNE (IF/IAF) (FB)	6300
3.	106/30 CW 196/30	IYIPE (IAF) (FB)	8200
4.	196/30 CW 286/30	HULUD (IAF) (FB)	8400

QUALITY
20
CHECKED

CITY AND STATE
COLDFOOT, AK

ELEVATION: 1046 TDZE: 1044
AIRPORT NAME:
COLDFOOT

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 2, AMDT 2
12 OCTOBER 2017

SUP: RNAV (GPS) RWY 1
AMDT: 1C
DATED: 12/10/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PACX
RUNWAY	RW02
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W02A
LTP/FTP LATITUDE	671451.1880N
LTP/FTP LONGITUDE	1501241.0380W
LTP/FTP ELLIPSOIDAL HEIGHT	+03228
FPAP LATITUDE	671606.3210N
FPAP LONGITUDE	1501038.8380W
THRESHOLD CROSSING HEIGHT (TCH)	00000.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	00.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1536
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 510FE696

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PA
LTP ORTHOMETRIC HEIGHT	+03150
FPAP ORTHOMETRIC HEIGHT	+03150

QUALITY
20
CHECKED

CITY AND STATE COLDFOOT, AK	ELEVATION: 1046 AIRPORT NAME: COLDFOOT	TDZE: 1044 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 2, AMDT 2 12 OCTOBER 2017	SUP: RNAV (GPS) RWY 1
				AMDT: 1C
				DATED: 12/10/2015